


About : cable information
 Version : 0.1
 File : For internal use only



Stainless steel probe assembly with SMT172 temperature sensor (part no: SMTRVS1802)



This probe is especially designed for use in combination with the Smartec SMT172 sensors. For specification of the sensor please look into the sensor specification as available on our website. Standard cable length is 5 meter please contact us when another cable or probe length is requested. Other stainless steel cable tips on request.

- | | | |
|--|-----------------|---|
| 1 | sensing element | SMT172-T018 |
| 3 | probe tip | Ø7x45 mm (ss. ANSI 303) |
| | sealing | Polyurethane resin |
| 4 | heat shrink | adhesive shrink sleeve |
| 5 | cable | 3x0.22mm ² shielded, shield NOT connected to probe tip (FEP/C/FEP); max temp 125°C |
| | cable length: | 500 mm other length on request |
| 6 | sleeve | polyolefin shrink sleeve |
| 7 | cable end | non-isolated splice (40mm) |
| connection: | | |
| | White | out |
| | Brown | Vcc |
| | Green | GND |
| Black(shrink) shield indication | | |
| (inside tube a capacitor of 100 nF is mounted) | | |

- 1 -

SMARTEC BV, Delpratsingel 26
 4811 AP BREDA, The Netherlands

WWW.SMARTEC-SENSORS.COM
 Tel: +31 (0)76 5205353

We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Office North America:

Angst+Pfister North America Inc.
10391 Brecksville Rd.
US-Brecksville, OH 44141
Phone +1 440 375-5212
info.apus@angst-pfister.com

Scan here and get an overview of personal contacts!



<https://sensorsandpower.angst-pfister.com/en/>
