

## Specification Sheet

Part Number: 596-00847

Made with UV stable inks and materials for durability and weather resistance

The labels are supplied with aggressive adhesive to ensure long life

Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections

**⚠ WARNING  
INVERTER OUTPUT  
CONNECTION. DO  
NOT RELOCATE  
THIS OVERCURRENT  
DEVICE.**

Solar Label, WARNING INVERTER OUTPUT...OVERCURRENT DEVICE, 2.0" x 1.25", VL, Red, 50/roll

Article Number 596-00847

Type IOCOD11

Color Red (RD)

Quantity Per reel

Product Description Many times common solar label designs are specified even though they might not be required by code. HellermannTyton offers a selection of some of the most commonly requested labels for use on solar installations.

Short Description Solar Label, WARNING INVERTER OUTPUT...OVERCURRENT DEVICE, 2.0" x 1.25", VL, Red, 50/roll

Global Part Name IOCOD11-V-RD

|                                |                                  |
|--------------------------------|----------------------------------|
| Length L (Imperial)            | 1.25                             |
| Length L (Metric)              | 31.75                            |
| Width W (Imperial)             | 2.0                              |
| Width W (Metric)               | 50.8                             |
| Height H (Imperial)            | 1.25                             |
| Height H (Metric)              | 31.75                            |
| Material                       | Vinyl (V)                        |
| Material Shortcut              | V                                |
| Adhesive                       | Acrylic                          |
| Halogen Free                   | No                               |
| UV Resistant (Yes/No)          | No                               |
| Use Conditions                 | For Indoor and Outdoor Use       |
| Adhesive Operating Temperature | -40°F to +174°F (-40°C to +79°C) |
| Operating Temperature          | -40°F to +174°F (-40°C to +79°C) |
| Reach Compliant (Article 33)   | Yes                              |

|                             |            |
|-----------------------------|------------|
| ROHS Compliant              | Yes        |
| Certification/Specification | NEC2011    |
| Warranty (US)               | Yes        |
| UL Recognized (US)          | Yes        |
| Package Quantity (Imperial) | 50         |
| Package Quantity (Metric)   | 50         |
| Customs Number              | 3919102055 |
| Labels per Column           | 1          |
| Labels per Row              | 1          |