

Specification Sheet

Part Number: 596-00253

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC® code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

RATED MAX POWER-POINT CURRENT	<input type="text"/>
RATED MAX POWER-POINT VOLTAGE	<input type="text"/>
MAXIMUM SYSTEM VOLTAGE	<input type="text"/>
MAXIMUM CIRCUIT CURRENT	<input type="text"/>
MAX RATED OUTPUT CURRENT OF THE CHARGE CONTROLLER IF INSTALLED	<input type="text"/>

Solar Label, Printable, DC Module, 4.0" x 2.0", PET, Red, 50/roll

Article Number 596-00253

Type DC2011

Color Red (RD)

Quantity Per reel

Product Description Designed with cross-laminated UV stable materials, these variable print Solar Installation Labels are designed to accept printing from any standard thermal transfer printer using a resin-based ink ribbon for the best durability. Print your voltage information directly on the label and then laminate with an optional clear acrylic laminate material for added protection. These labels can be used to print disconnecting means and breaker series directly on the labels for a more professional result and a smoother inspection process.

Short Description	Solar Label, Printable, DC Module, 4.0" x 2.0", PET, Red, 50/roll
Global Part Name	DC2011-840/281-RD
Local Order Number 2	Cross Reference = 10 per pack: 596-00850; Printable Metal Solar Placard 5 pack: 596-00839; Engravable Metal Solar Placard 5 pack: 596-00863; Spanish version 50 per roll: 596-00817
Width W (Imperial)	4.0
Width W (Metric)	101.6
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	2.0
Height H (Metric)	50.8
Material	Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)
Material Shortcut	840/281
Adhesive	Acrylic
Halogen Free	Yes
UV Resistant (Yes/No)	Yes

Use Conditions	For Indoor and Outdoor Use
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	NEC2014 UL 969 IFC 2012 CSA 66956
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1