

Specification Sheet

Part Number: 596-00652

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

PHOTOVOLTAIC AC DISCONNECT
MAXIMUM AC OPERATING CURRENT: <input type="text"/>
NOMINAL OPERATING AC VOLTAGE: <input type="text"/>

Solar Label, Printable, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll

Article Number 596-00652

Type PVACDIS-1

Color Red (RD)

Quantity Per reel

Product Description
Designed in a one-across landscape format to fit into the compact TT130SMC thermal transfer printer, these labels allow for code-compliant marking of variable information including disconnecting means, breaker series and voltage data. Made with cross-laminated UV stable materials, labels are ideal for use in solar installation applications. Use with the TT130SMC or any HellermannTyton thermal transfer printer.

Short Description	Solar Label, Printable, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll
Global Part Name	PVACDIS-1-840/281-RD
Width W (Imperial)	1.0
Width W (Metric)	25.4
Thickness T (Metric)	64.0
Height H (Imperial)	3.75
Height H (Metric)	95.25
Material	Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)
Material Shortcut	840/281
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)

Operating Temperature -40°F to +302°F (-40°C to +150°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Certification/Specification UL 969

UL Recognized (US) Yes

Package Quantity (Imperial) 50

Package Quantity (Metric) 50

Customs Number 3919102055

Labels per Column 1

Labels per Row 1