

## Specification Sheet

Part Number: 596-00655

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

NOMINAL OPERATING AC VOLTAGE	<input type="text"/>
NOMINAL OPERATING AC FREQUENCY	<input type="text"/>
MAXIMUM AC POWER	<input type="text"/>
MAXIMUM AC CURRENT	<input type="text"/>
MAX OVERCURRENT DEVICE RATING FOR AC MODULE PROTECTION	<input type="text"/>

Solar Label, Printable, AC MODULE, 4.0" x 2.0", PET, Red, 50/roll

Article Number 596-00655

Type AC2011-1

Color Red (RD)

Quantity Per reel

**Product Description** Designed in a one-across landscape format to fit into the compact TT130SMC thermal transfer printer, these labels allow for code-compliant marking of variable information including disconnecting means, breaker series and voltage data. Made with cross-laminated UV stable materials, labels are ideal for use in solar installation applications. Use with the TT130SMC or any HellermannTyton thermal transfer printer.

Short Description	Solar Label, Printable, AC MODULE, 4.0" x 2.0", PET, Red, 50/roll
Global Part Name	AC2011-1-840/281-RD
Width W (Imperial)	2.0
Width W (Metric)	50.8
Thickness T (Metric)	64.0
Height H (Imperial)	4.0
Height H (Metric)	101.6
Material	Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)
Material Shortcut	840/281
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)

Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL 969
UL Recognized (US)	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1