



Quality Products. Service Excellence.

Hospital-Grade Outlet Strip 1584H Series

15A | 125V | 5-15R-HG Outlets

Features



- Featuring a sturdy aluminum extruded case with a distinctive black powder paint coated steel cover.
- Designed to meet the special requirements for institutional and chronic care use with "Hospital Grade" white receptacles, line cord and plug.
- These devices are intended for non-patient connected indoor applications to providing power to electronic equipment.
- These devices are not intended to be used to supply power to life-support appliances, and not for use in critical care environments.
- Exceeds NEMA requirements for low leakage ground return and for withstanding impact or continuous physical shock without loss of grounding path continuity when plugged into properly grounded source receptacles.
- The white "Hospital Grade" receptacles are securely fastened onto the housing and interconnected with solidly bonded bus bars. All bus bars are double connected with a convection pressure sensitive clamp and safety screw.
- **Perfect for ground sensitive audio applications!**
- An additional grounding stud is provided on the case for any further external grounding requirements.
- Mounting feet (with keyhole slots) allow temporary work station mounting if desired.

Specifications

- Heavy duty 14 gauge cord - 14/3 SJT for extreme temperature ranges and integral clear molded "Hospital Grade" plug.
- Receptacles are NEMA 5-15R-HG.
- Complete with a 15 amp, 125 volt resettable circuit breaker to prevent accidental line overload.
- CSA certified, Standards C22.2 (No. 21-95 and No. 42-99), CSA Cord Sets No. 8 (Hospital Grade Powerbars).
- TUVus certified to UL60601-1 (medical grade) and UL 1363 (relocatable power taps).
- TAA compliant for GSA Schedule purchases.
- RoHS Compliant.
- Manufactured in North America.

Accessories

- Rack Cabinet Vertical Mount Adaptor

| Part No. | Overall Dimensions | | | Outlets | Cord Length (ft) |
|-----------|--------------------|-------|--------|---------|------------------|
| | Height | Width | Length | | |
| 1584T4DH6 | 2.33 | 2.12 | 10.18 | 4 | 6 |
| 1584T4DH | 2.33 | 2.13 | 10.18 | 4 | 12 |
| 1584T6DH6 | 2.33 | 2.12 | 13.36 | 6 | 6 |
| 1584T6DH | 2.33 | 2.13 | 13.36 | 6 | 12 |

| Part No. | Overall Dimensions | | | Outlets | Cord |
|-----------|--------------------|-------|--------|---------|-------------|
| | Height | Width | Length | | Length (ft) |
| 1584T8DH6 | 2.33 | 2.12 | 16.51 | 8 | 6 |
| 1584T8DH | 2.33 | 2.13 | 16.51 | 8 | 12 |

Replacement Mounting Foot (One Foot)

| | |
|----------|--------|
| Part No. | 1584MF |
|----------|--------|

Data subject to change without notice

© 2025. Hammond Manufacturing Ltd. All rights reserved.