

6-Outlet Surge Protector Tower, 3x USB-A, 1x USB-C, 8 ft. Cord, 5-15P Plug, 1800 Joules, Black

MODEL NUMBER: TLP606UCTOWER



Surge protection tower with USB charging safeguards your electronics against dangerous surges, spikes and line noise.

Features

6-Outlet Surge Protection Tower Safeguards Your Sensitive Electronics

Ideal for your home or office workstation, this Protect It!® six-outlet tower features a surge suppression rating of 1800 joules to defend your sensitive electronic components against even the strongest power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP606UCTOWER protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

6 NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your laptop, external hard drive, desk lamp and other home/office devices into the NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. The outlets are split between three sides of the tower and spread apart to allow easy connection of bulky transformers without blocking adjacent outlets.

USB Ports Share 6 Amps of Charging Power

Three USB-A ports, as well as one USB-C port, are available for charging your smartphone, tablet and other USB mobile devices. They share 6A for charging multiple devices at the same time.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Includes the Latest Safety Features to Maintain Your Equipment's Well-Being

An on/off switch allows you easy one-touch control over all connected equipment. The green LED confirms at a glance that your plugged-in devices are protected.

Versatile Tower Design Gives You Plenty of Options for Installation and Use

The TLP606UCTOWER fits easily into your home or office workspace, conference table or classroom, providing power and USB charging at your fingertips. The braided eight-foot power cord and space-saving right-angle NEMA 5-15P plug allow connection in tight spaces, such as behind furniture.

Highlights

- Ideal for conference tables, home offices and other areas with multiple mobile devices
- 6 NEMA 5-15R outlets spaced widely apart to accommodate bulky transformers
- 1800 joules protect your valuable electronics against dangerous surges and spikes
- USB-C and USB-A ports provide fast charging of phones, tablets and other mobile devices
- Right-angle NEMA 5-15P plug with braided 8 ft. cord allows connection in tight spaces

Applications

- Ensure critical devices, such as laptops and tablets, stay fully powered and charged during important conferences and meetings
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against damage stemming from unexpected surges
- Charge a smartphone and tablet via USB without taking up available AC outlets

Package Includes

- TLP606UCTOWER 6-Outlet Surge Protector Tower, Black
- Owner's manual



Powering Business Worldwide



Specifications

OVERVIEW	
UPC Code	037332260307
Device Compatibility	Phone; Tablet
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Input Cord Gauge (AWG)	14
Input Plug Type	NEMA 5-15P
Input Cord Details	SJT-B
Input Cord Length (ft.)	8
Right-Angle Plug	No
Input Cord Length (m)	2.44
Integrated Cord Clip	No
OUTPUT	
Frequency Compatibility	60 Hz
Output (Watts)	1800
Output Receptacles	(6) 5-15R
Circuit Breaker (amps)	15
Overload Protection	Yes
Transformer Accommodation	Yes
Right-Angle Outlets	No
USER INTERFACE, ALERTS & CONTROLS	
Diagnostic LED(s)	Yes
Diagnostic LED Details	Yes
CHARGING	
Number of Charging Ports	4
Total Charging Watts	30.5
Charging Method	USB
Charging Port Type	(3) USB A (FEMALE); (1) USB C (FEMALE)
Charging Ports / Amps	(3) 3.1A; (1) 3A
Overcharge Protection	No
SURGE / NOISE SUPPRESSION	



Powering Business Worldwide



AC Suppression Joule Rating	1800
AC Suppression Response Time	< 1 ns
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
UL1449 Let Through Rating	L-N, L-G, N-G 800,800,800
EMI / RFI Filtering	Yes
Immunity	Conforms to IEE 587/ANSI C62.41
Automatic Shut-Off	No
DATALINE SURGE SUPPRESSION	
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
Telephone/DSL Protection	No
PHYSICAL	
Material of Construction	Plastic
Power Cord Color	Black and Gray Braided
Mounting Holes or Slots	No
Receptacle Color	Gray
Unit Dimensions (hwd / in.)	7.800 x 5.900 x 4.000
Unit Dimensions (hwd / cm)	19.8 x 14.9 x 10.6
Unit Weight (lbs.)	2.3
Unit Weight (kg)	1.04
FEATURES & SPECIFICATIONS	
Rotatable Outlets	No
Antimicrobial	No
GaN Technology	No
STANDARDS & COMPLIANCE	
Product Certifications	CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 497A; UL 1363; UL Listed
Product Compliance	FCC Part 68; RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$10,000 Ultimate Lifetime Insurance



Powering Business Worldwide



1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.