

## 5.5kW Single-Phase Local Metered PDU, 208/230V Outlets (6-C19 & 24-C13), L6-30P, 10 ft. (3.05 m) Cord, 0U Vertical

MODEL NUMBER: PDUMV30HV



### Features

- 30A single phase 208/230V Local Metered Power Distribution Unit / rack PDU (rPDU) (Agency derated to 24A continuous)
- Set of two lighted meters report PDU output current in amps for each output load bank
- Attached NEMA L6-30P 30A 208/230V input plug and 10ft / 3m cord
- 0U 63.75in / 162cm vertical rackmount format installs using no rack spaces
- 30 output receptacles (6 C19, 24 C13)
- Outlets are arranged in two 15 outlet load banks, each with separate 15A breaker and current metering
- Toolless installation in button-mount compatible equipment racks
- Included plug-lock inserts ensure components remain connected and powered

### Highlights

- Local metered single phase 24A 208/230V, 0U 63.75in / 162cm vertical rackmount PDU
- Pair of digital meters report output current in amps for each load bank
- Attached 10ft / 3m cord with NEMA L6-30P input plug
- 30 outlets (6 C19, 24 C13) in two separately breakered load banks
- Ready for immediate toolless 0U installation

### Package Includes

- PDUMV30HV 63.75 inch Local Metered PDU
- Plug-lock inserts (6 C20, 24 C14)
- Spare installation buttons, 2.9 mm/4.6 mm
- Set of mounting brackets and installation hardware
- Owner's Manual

## Specifications

| OVERVIEW                       |                                   |
|--------------------------------|-----------------------------------|
| UPC Code                       | 037332139351                      |
| PDU Type                       | Local Metered                     |
| INPUT                          |                                   |
| Input Phase                    | Single-Phase                      |
| PDU Input Voltage              | 208; 230                          |
| Recommended Electrical Service | Single-phase 30A 208/230V service |
| Maximum Input Amps             | 24                                |
| Maximum Input Amps Details     | Agency de-rated to 24A continuous |



Powering Business Worldwide

TRIPP LITE  
SERIES

|  |   |
|--|---|
| PDU Plug Type                                | NEMA L6-30P   |
| Input Cord Length (ft.)                      | 10  |
| Input Cord Length (m)                        | 3.05  |
| <b>OUTPUT</b>                                |   |
| Output Capacity (kW)                         | 5.5   |
| Output Capacity Details                      | 5.5kW (230V), 5kW (208V) total capacity / 30A max (Agency de-rated to 24A), 15A max per breaker outlet bank; 12A max per C13 outlet     |
| Frequency Compatibility                      | 50 / 60 Hz  |
| Output Receptacles                           | (24) C13; (6) C19   |
| Output Nominal Voltage                       | 208/230V  |
| Overload Protection                          | Two 15A breakers protect 15 outlets each  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Front Panel LCD Display                      | Set of 2 digital current meters continuously report PDU output current in amps for Bank 1 (15A max) and Bank 2 (15A max) outlets        |
| Front Panel LEDs                             | Includes 2 built-in 2-character LED meters to display power consumption of items plugged into each separately breaker 15A loading bank. |
| <b>SURGE / NOISE SUPPRESSION</b>             |   |
| Automatic Shut-Off                           | No  |
| <b>PHYSICAL</b>                              |   |
| Material of Construction                     | Aluminum  |
| Rack Height                                  | 0U  |
| Form Factors Supported                       | 0U vertical installation in equipment racks, plus under-counter and wallmount   |
| PDU Form Factor                              | Vertical (0U)   |
| Shipping Dimensions (hwd / in.)              | 5.00 x 3.00 x 65.00   |
| Shipping Dimensions (hwd / cm)               | 12.70 x 7.62 x 165.10   |
| Shipping Weight (lbs.)                       | 11.40   |
| Shipping Weight (kg)                         | 5.17  |
| Unit Dimensions (hwd / in.)                  | 63.750 x 3.500 x 2.250  |
| Unit Dimensions (hwd / cm)                   | 162 x 5.7 x 9.5   |
| Unit Weight (lbs.)                           | 8.00  |
| Unit Weight (kg)                             | 3.63  |
| <b>ENVIRONMENTAL</b>                         |   |
| Operating Temperature Range                  | 32° to 104°F (0° to 40°C)   |
| Storage Temperature Range                    | -22° to 122°F (-30° to 50°C)  |
| Relative Humidity                            | 0% to 95% non-condensing  |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                     |  |
|-------------------------------------|--|
| Operating Elevation                 | 0-10000 ft. (0-3000 m)                     |
| <b>STANDARDS &amp; COMPLIANCE</b>   |  |
| Product Certifications              | RETIE (Colombia); NOM (Mexico); UL 62368-1 |
| Product Compliance                  | RoHS; FCC Part 15 Class A (USA)            |
| <b>WARRANTY &amp; SUPPORT</b>       |  |
| Product Warranty Period (Worldwide) | 2-year limited warranty                    |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.