

Personal Desktop Charging Station with 2-Outlet Surge Protector, 6 ft. (1.83 m) Cord, 1080 Joules, 4 x USB (4.8A total)

MODEL NUMBER: TLP26USBB



Highlights

- 2 outlet / 6-ft. cord
- 1080 joule rating
- 4.8 amp quad port USB charger

Package Includes

- TLP26USBB Personal Desktop Charging Station
- Instruction manual with warranty information

Description

The TLP26USBB Personal Desktop Charging Station provides exceptional convenience for daily charging tasks. Perfect for home, office, workstations and dorm rooms. With two AC outlets for safe power and four USB ports with 4.8 amps of total power, this charging station can easily handle multiple devices. The built-in slot can hold your tablet or phone for hands-free viewing while charging. The TLP26USBB offers two total outlets, a six-foot power cord, four USB charging ports for a total of 4.8 amps and a diagnostic LED to warn of suppressor damage. AC suppression rated at 1080 joules shields equipment from surges and line noise.

Features

- 2 outlets
- 6-ft. (1.83 m) cord
- 4 USB charging ports - 4.8 amp total
- Built in slot to hold phones and tablets
- Surge suppression rating: 1080 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Green protection LED
- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332183385 |



Powering Business Worldwide



| | |
|--|--|
| Product Type | Surge Protector |
| Charging Form Factor | Strip |
| Device Compatibility | Phone; Tablet; Amazon Kindle |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V (110-125V) |
| Input Cord Gauge Type | 16 gauge; SJT |
| Input Cord Gauge (AWG) | 16; SJT |
| Voltage Compatibility (VAC) | 120 |
| Input Plug Type | NEMA 5-15P |
| Input Cord Details | SJT |
| Input Cord Length (ft.) | 6 |
| Right-Angle Plug | Yes |
| Input Cord Length (m) | 1.83 |
| Integrated Cord Clip | No |
| OUTPUT | |
| Frequency Compatibility | 60 Hz |
| Output (Watts) | 1800 |
| Output Receptacles | (2) 5-15R |
| Circuit Breaker (amps) | 15 |
| Right-Angle Outlets | No |
| USER INTERFACE, ALERTS & CONTROLS | |
| Diagnostic LED(s) | Yes |
| Diagnostic LED Details | Built-in LED confirms suppressor "protection present" (green) status |
| CHARGING | |
| Number of Charging Ports | 4 |
| Total Charging Watts | 24 |
| Charging Method | USB |
| Charging Port Type | USB A (FEMALE) |
| Charging Ports / Amps | (4) 4.8A |
| Overcharge Protection | No |
| SURGE / NOISE SUPPRESSION | |
| AC Suppression Joule Rating | 1080 |



Powering Business Worldwide



| | |
|--------------------------------------|--|
| AC Suppression Response Time | < 1 ns |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| UL1449 Let Through Rating | 400V |
| EMI / RFI Filtering | Yes |
| Automatic Shut-Off | Yes |
| DATALINE SURGE SUPPRESSION | |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| Telephone/DSL Protection | No |
| PHYSICAL | |
| Material of Construction | Plastic |
| Power Cord Color | Black |
| Housing Color | Black |
| Mounting Holes or Slots | No |
| Receptacle Color | Black |
| Shipping Dimensions (hwd / in.) | 3.60 x 6.50 x 5.80 |
| Shipping Dimensions (hwd / cm) | 9.14 x 16.51 x 14.73 |
| Shipping Weight (lbs.) | 1.60 |
| Shipping Weight (kg) | 0.73 |
| Unit Dimensions (hwd / in.) | 1.420 x 5.210 x 5.210 |
| Unit Dimensions (hwd / cm) | 3.61 x 13.23 x 13.23 |
| Unit Weight (lbs.) | 1.2 |
| Unit Weight (kg) | 0.54 |
| Input Cord Color | Black |
| FEATURES & SPECIFICATIONS | |
| Rotatable Outlets | No |
| Antimicrobial | No |
| GaN Technology | No |
| STANDARDS & COMPLIANCE | |
| Product Certifications | CAN/CSA-C22.2 No. 269.3 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL Listed |
| Product Compliance | RoHS |
| WARRANTY & SUPPORT | |



Powering Business Worldwide



| | |
|--|---|
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$50,000 & Ultimate Lifetime Insurance |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.