

## Eco-Surge 10-Outlet Surge Protector, 8-ft. Swivel Cord, 6480 Joules, Tel/Modem/Coax/Ethernet Protection

MODEL NUMBER: **AV10IRG**



### Highlights

- 6,480 joules of advanced surge protection for medium-to-large home/business theater installations
- 10 outlets, 3-line coaxial and 1-line tel/network protection
- 8-ft. swivel cord, 6-ft. coaxial cable and 6-ft. network cable
- ECO-SURGE feature saves energy by disabling AC power to unused POWERSAVE outlets

### Package Includes

- AV10IRG ECO-SURGE Energy Saving Surge Suppressor
- 6-ft. tel/network cable
- 6-ft. gold coaxial cable

### Description

Do you need a quality surge protection for equipment in your home/business theater such as high definition TVs, satellite A/V receivers, DVD/CD players, DVR/Tivo recorders, and has energy-saving capabilities as well? Then Tripp Lite's AV10IRG ECO-Surge Suppressor featuring reliable, power-saving, GREEN surge technology is a great choice. The AV10IRG offers 6,480 joules of advanced surge protection. You will see and hear the difference: sharper, crisper video; deeper, fuller audio; longer component life spans. It can safeguard your entire home theater system in a robust 10-outlet, 3-line 2.2 GHz digital gold coaxial protection and 1-line tel/network protection package; it also includes 3 diagnostic LEDs, 4 status LEDs, an 8-ft. swivel cord, a 6-ft. coaxial cable and a 6-ft. network cable. To save energy, the AV10IRG is designed with an energy-saving outlet configuration that reduces energy waste (phantom loads) by cutting AC power to unused peripherals. To enable the GREEN "Power Save" outlets, the AV10IRG has an IR receiver embedded in its front panel that can receive a turn-on signal from any IR remote. The AV10IRG has a sleek, contemporary design, and a LCD screen that fits into any A/V installation. For peace of mind, the AV10IRG comes with \$250,000 Ultimate Lifetime Insurance coverage (U.S., Canada, and Puerto Rico only).

### Features

#### Premium Level of Surge Protection

- 6,480-joule surge suppression rating with EMI/RFI line noise filtering to help components perform at their peak (i.e. sharper, crisper video; deeper, fuller audio and longer component life spans)
- 1-line of tel/modem/Ethernet (100BaseT, high-speed) surge protection safeguards personal video recorders (PVRs) on a single dial-up or Ethernet line.
- 3-lines of surge-protected, 2.2 GHz gold coaxial connectors to safeguard devices on cable, satellite and antenna lines

#### Extra Long Power Cord

- 8-ft, NEMA 5-15P, swivel power cord reaches around corners, obstacles or can access distant outlets



Powering Business Worldwide



#### NEMA-Rated, Protected Outlets

- 10 rear-facing, NEMA 5-15R, surge-protected outlets (7 ECO-SURGE protected and 3 ALWAYS ON protected)

#### Diagnostic LED Indicators

- 3 diagnostic LEDs to alert users to the power, protection and safety-ground status
- 4 status LEDs to indicate when AC power is present.
- An illuminated LED panel shows real time amperage readings of the 7 "Power Save" outlets, helping to avoid power overloads

#### ECO-Surge Technology

- ECO-Surge, "Power Save" Green Outlet Array switches off AC power approximately 3 minutes after the internal GREEN "Power Save" technology detects the total power consumption of the "Power Save" outlets has dropped 70%. "Power Save" outlets are recommended for intermittent-use devices such as TVs, receivers, monitors, printers, scanners, lamps, DVD players, gaming consoles, amplifiers and speaker systems
- "Always On" outlets provide continuous power even after the "Power Save" outlets are turned OFF. These outlets are recommended for 3 critical devices that save settings such as DVRs and recorders (TiVo), cable and satellite boxes
- IR receiver receives a turn-on signal from any standard IR remote to energize devices plugged into the GREEN "Power Save" outlets
- IR extension jack works with an optional cord and small receiver to extend IR transmission distance. [IR Extender Referral Link](#)

## Specifications

| OVERVIEW                           |                 |
|------------------------------------|-----------------|
| UPC Code                           | 037332155627    |
| INPUT                              |                 |
| Nominal Input Voltage(s) Supported | 120V AC         |
| Recommended Electrical Service     | 120V (110-125V) |
| Input Cord Gauge Type              | 14 gauge; SJT   |
| Voltage Compatibility (VAC)        | 120             |
| Maximum Surge Amps                 | 432000          |
| Input Plug Type                    | NEMA 5-15P      |
| Input Cord Length (ft.)            | 8               |
| Right-Angle Plug                   | No              |
| Input Cord Length (m)              | 2.44            |
| Integrated Cord Clip               | No              |
| OUTPUT                             |                 |
| Frequency Compatibility            | 60 Hz           |



Powering Business Worldwide

**TRIPP-LITE**  
by **EAT•N**

|                                              |                                                                                    |
|----------------------------------------------|------------------------------------------------------------------------------------|
| Output (Watts)                               | 1800                                                                               |
| Output Receptacles                           | (10) 5-15R                                                                         |
| Outlet Orientation                           | 10 rear outlets (7 controlled, 3 unswitched)                                       |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                                                                                    |
| Diagnostic LED(s)                            | Yes                                                                                |
| <b>SURGE / NOISE SUPPRESSION</b>             |                                                                                    |
| AC Suppression Joule Rating                  | 6480                                                                               |
| AC Suppression Response Time                 | <1                                                                                 |
| Protection Modes                             | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| UL1449 Let Through Rating                    | 330V                                                                               |
| EMI / RFI Filtering                          | Up to 75 dB                                                                        |
| Automatic Shut-Off                           | Yes                                                                                |
| <b>DATALINE SURGE SUPPRESSION</b>            |                                                                                    |
| Telephone/DSL Protection Details             | 1 line                                                                             |
| Cable (Coax) Protection                      | Yes                                                                                |
| Cable (Coax) Protection Details              | 3 line                                                                             |
| Network (Ethernet) Protection                | Yes                                                                                |
| Telephone/DSL Protection                     | Yes                                                                                |
| <b>PHYSICAL</b>                              |                                                                                    |
| Color                                        | Black                                                                              |
| Power Cord Color                             | Black                                                                              |
| Housing Color                                | Black                                                                              |
| Mounting Holes or Slots                      | No                                                                                 |
| Receptacle Color                             | Black                                                                              |
| Shipping Dimensions (hwd / in.)              | 7.50 x 2.60 x 18.60                                                                |
| Shipping Dimensions (hwd / cm)               | 19.05 x 6.60 x 47.24                                                               |
| Shipping Weight (lbs.)                       | 4.30                                                                               |
| Shipping Weight (kg)                         | 1.95                                                                               |
| Unit Dimensions (hwd / in.)                  | 1.730 x 4.370 x 17.360                                                             |
| Unit Dimensions (hwd / cm)                   | 4.39 x 11.10 x 44.09                                                               |
| Unit Weight (lbs.)                           | 3.11                                                                               |
| Unit Weight (kg)                             | 1.41                                                                               |
| <b>FEATURES &amp; SPECIFICATIONS</b>         |                                                                                    |

|                                                            |                                                                                                                                     |
|------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Green Energy-Saving Features                               | Power saving auto-shutoff ECO outlets                                                                                               |
| Rotatable Outlets                                          | No                                                                                                                                  |
| Antimicrobial                                              | No                                                                                                                                  |
| WARRANTY & SUPPORT                                         |                                                                                                                                     |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty                                                                                                           |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$250,000&nbsp;<a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp; |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.