

## TAA-Compliant Internet Office 120V 600VA 300W Standby UPS, Ultra-Compact Desktop, USB

MODEL NUMBER: INTERNET600TAA



### Highlights

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 600VA ultra-compact 120V standby UPS
- 4 UPS battery supported outlets, 4 surge-only outlets
- USB, TEL/DSL protection, Wall mountable, 99% efficient
- NEMA 5-15P input plug and 8 NEMA 5-15R outlets
- **This product is ENERGY STAR qualified for its ability to save customers money while helping to protect the environment**

### Package Includes

- INTERNET600TAA UPS system
- USB cable
- Instruction manual

### Description

Ultra-compact standby UPS with built-in USB monitoring port protects PCs, network workstations and other systems reliant upon a USB interface for UPS monitoring and unattended system shutdown. Maintains AC output during blackouts and brownouts starting at 99V. Includes USB monitoring with cabling, TEL/DSL line surge suppression, surge-only outlets and LED indicators. PowerAlert software available free via download.

### Features

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- This product is ENERGY STAR qualified for its ability to save customers money while helping to protect the environment
- INTERNET600TAA standby UPS offers protection from blackouts, brownouts and surges on both AC and dialup modem lines
- Provides seamless battery derived AC output during blackouts and severe brownouts so that connected equipment can be shut down without data loss
- USB port enables data-saving unattended shutdown when used with Tripp Lite's PowerAlert software, available via FREE download from [tripplite.eaton.com/products/power-alert](http://tripplite.eaton.com/products/power-alert)
- HID-compliant USB also enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- 4 battery supported outlets protect computer, monitor and other vital system peripherals, plus 4 additional surge suppression-only outlets for printers and other system accessories not requiring battery support
- Attractive stealth black UPS color scheme
- Single line phone jacks with line splitter protects peripherals with a standard dialup phone line connection
- Audible alarm and front panel LEDs offer continuous status information regarding line and battery power operation
- 600VA /300 watt power handling ability supports entry-level PC systems for several minutes during power fail conditions
- Includes attached 6 ft. AC power cord, on/off power switch
- Compatible with 120V/60 Hz applications in USA, Canada, Mexico and other countries



Powering Business Worldwide



- Optional PDUB15 bypass PDU enables hot-swappable UPS replacement with no disruption to connected equipment

## Specifications

| OVERVIEW                                        |                                     |
|-------------------------------------------------|-------------------------------------|
| UPC Code                                        | 037332184092                        |
| UPS Type                                        | Standby                             |
| INPUT                                           |                                     |
| Input Phase                                     | Single-Phase                        |
| Rated input current (Maximum Load)              | 10A                                 |
| Nominal Input Voltage(s) Supported              | 120V AC                             |
| UPS Input Connection Type                       | 5-15P; Right-Angled                 |
| Input Circuit Breakers                          | 10A                                 |
| UPS Input Cord Length (ft.)                     | 6                                   |
| UPS Input Cord Length (m)                       | 1.8                                 |
| Recommended Electrical Service                  | 15A 120V                            |
| OUTPUT                                          |                                     |
| Output Capacity (VA)                            | 600                                 |
| Output Capacity (Watts)                         | 300                                 |
| Nominal Voltage Details                         | 115v nominal output in battery mode |
| Frequency Compatibility                         | 60 Hz                               |
| Output Voltage Regulation (Battery Mode)        | +/- 5%                              |
| UPS Output Receptacles (Surge Suppression Only) | 4 UPS outlets, 4 surge-only outlets |
| Hot-Swap PDU options                            | PDUB15 (2U / 8 5-15R outlets)       |
| Output AC Waveform (AC Mode)                    | Sine wave                           |
| Output AC Waveform (Battery Mode)               | PWM sine wave                       |
| Nominal Output Voltage(s) Supported             | 110V; 115V; 120V                    |
| Output Receptacles                              | (8) 5-15R                           |
| BATTERY                                         |                                     |
| Runtime Full Load (min.)                        | 3.4 min.                            |
| Runtime Half Load (min.)                        | 9.9 min.                            |
| Expandable Runtime                              | No                                  |



Powering Business Worldwide

**TRIPP-LITE**  
by **EAT•N**

|                                                               |                                                                         |
|---------------------------------------------------------------|-------------------------------------------------------------------------|
| DC System Voltage (VDC)                                       | 12                                                                      |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>                  |                                                                         |
| Switches                                                      | Combination switch controls on/off power status and self-test operation |
| Audible Alarm                                                 | Audible alarm indicates power-failure and overload status               |
| LED Indicators                                                | 2 LEDs indicate power status and overload/check battery status          |
| <b>SURGE / NOISE SUPPRESSION</b>                              |                                                                         |
| UPS AC Suppression Joule Rating                               | 420                                                                     |
| UPS AC Suppression Response Time                              | Instantaneous                                                           |
| UPS Dataline Suppression                                      | 1 line TEL/DSL (1 in / 1 out)                                           |
| EMI / RFI AC Noise Suppression                                | Yes                                                                     |
| <b>PHYSICAL</b>                                               |                                                                         |
| Primary Form Factor                                           | Desktop                                                                 |
| Included Mounting Accessory Description                       | Wallmount installation supported using keyhole mounting tabs            |
| Installation Form Factors Supported with Included Accessories | Tower; Ultra-compact desktop                                            |
| Primary UPS Depth (mm)                                        | 145                                                                     |
| Primary UPS Height (mm)                                       | 79                                                                      |
| Primary UPS Width (mm)                                        | 274                                                                     |
| Shipping Dimensions (hwd / in.)                               | 4.10 x 8.00 x 13.00                                                     |
| Shipping Dimensions (hwd / cm)                                | 10.41 x 20.32 x 33.02                                                   |
| Shipping Weight (lbs.)                                        | 7.00                                                                    |
| Shipping Weight (kg)                                          | 3.18                                                                    |
| UPS Housing Material                                          | ABS                                                                     |
| UPS Power Module Dimensions (hwd, cm)                         | 7.87 x 27.43 x 14.48                                                    |
| UPS Power Module Dimensions (hwd, in.)                        | 3.1 x 10.8 x 5.7                                                        |
| UPS Power Module Weight (kg)                                  | 2.95                                                                    |
| UPS Power Module Weight (lbs.)                                | 6.5                                                                     |
| <b>ENVIRONMENTAL</b>                                          |                                                                         |
| Operating Temperature Range                                   | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius.              |
| Storage Temperature Range                                     | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius.             |
| Relative Humidity                                             | 0 to 95%, non-condensing                                                |
| AC Mode BTU / Hr. (Full Load)                                 | 14                                                                      |



Powering Business Worldwide



|                                                             |                                                                                                                                                                                                                                             |
|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AC Mode Efficiency Rating (100% Load)                       | 99%                                                                                                                                                                                                                                         |
| Battery Mode Heat Dissipation (BTU/Hr) @ Full Load          | 210                                                                                                                                                                                                                                         |
| <b>COMMUNICATIONS</b>                                       |                                                                                                                                                                                                                                             |
| PowerAlert Software                                         | For local monitoring via the UPS's built-in USB port, download PowerAlert software at <a href="https://tripplite.eaton.com/products/power-alert">https://tripplite.eaton.com/products/power-alert</a>                                       |
| Communications Cable                                        | RJ to USB interface cable included                                                                                                                                                                                                          |
| WatchDog Compatibility                                      | Supports Watchdog application, OS and hard-reboot restart options for remote applications                                                                                                                                                   |
| Network UPS Tools (NUT) Compatibility                       | NUT compatible. See the full list of Tripp Lite NUT compatible UPS systems at <a href="https://www.networkupstools.org/stable-hcl.html?manufacturer=Tripp+Lite">https://www.networkupstools.org/stable-hcl.html?manufacturer=Tripp Lite</a> |
| Communications Interface                                    | USB (HID enabled)                                                                                                                                                                                                                           |
| <b>LINE / BATTERY TRANSFER</b>                              |                                                                                                                                                                                                                                             |
| Transfer Time                                               | 2-4 milliseconds                                                                                                                                                                                                                            |
| Low Voltage Transfer to Battery Power (Setpoint)            | 99                                                                                                                                                                                                                                          |
| High Voltage Transfer to Battery Power (Setpoint)           | 139                                                                                                                                                                                                                                         |
| <b>FEATURES &amp; SPECIFICATIONS</b>                        |                                                                                                                                                                                                                                             |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported                                                                                                                                                                                                              |
| Green Energy-Saving Features                                | Greater than 95% efficiency - GREEN UPS                                                                                                                                                                                                     |
| <b>WARRANTY &amp; SUPPORT</b>                               |                                                                                                                                                                                                                                             |
| Product Warranty Period (U.S. & Canada)                     | 3-year limited warranty                                                                                                                                                                                                                     |
| Product Warranty Period (Latin America)                     | 3-year limited warranty                                                                                                                                                                                                                     |
| Product Warranty Period (International)                     | 2-year limited warranty                                                                                                                                                                                                                     |
| Product Warranty Period (Mexico)                            | 3-year limited warranty                                                                                                                                                                                                                     |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico)  | \$100,000&nbsp;<a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp;                                                                                                         |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.