

VGA with Audio over Cat5/Cat6 Extender, Receiver, USB-Powered, 1440x900 60 Hz, Up to 300 ft. (90 m), TAA

MODEL NUMBER: **B132-100A-SR**



Extends a VGA video and audio signal up to 300-ft. (91M) from the source

Features

- Works with a B13 or B13 Transmitter Unit to extend a VGA video and audio signal up to 300-ft. from the source
- Extends a 1440 x 900 video and audio signal up to 150-ft, or a 1024 x 768 video and audio signal up to 300-ft.
- 24AWG, Solid Wire Cat5e/6 cable (such as Tripp Lite's N20 Cat6 cables) is required to achieve maximum distance and resolution
- Power is supplied via the included USB Micro-B cable; no external power supply required
- Features built-in equalization and gain controls to adjust the video image
- All operating systems supported
- Plug and play; no software or drivers required
- HDCP and EDID compliant
- Ideal for digital signage installations for retail, schools, churches, etc.
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
UPC Code	037332185563
Product Type	Receiver
Technology	VGA/SVGA; Stereo Audio; Cat5/5e; Cat6
VIDEO	

Highlights

- Works with a B132-002A-2 or B132-004A-2 Transmitter Unit to extend a VGA video and audio signal up to 300-ft. from the source
- Extends a 1440 x 900 video and audio signal up to 150-ft, or a 1024 x 768 video and audio signal up to 300-ft.
- Power is supplied via the included USB Micro-B cable; no external power supplies required
- Plug and play, no software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Package Includes

- B132-100A-SR
- USB Micro-B cable
- Screwdriver for EQ/Gain adjustment
- Owner's Manual



Powering Business Worldwide



Max 720P Range (ft)	150
HDR Support	No
3D Video Supported	No
Maximum Signal Range (ft)	300
Maximum Signal Range (m)	91
INPUT	
Bus Powered	No
POWER	
Power Over Cable (PoC) Support	No
CONNECTIONS	
Number of Ports	1
Side A - Connector 1	RJ45 (FEMALE)
Side B - Connector 1	HD15 (FEMALE)
Side B - Connector 2	3.5MM (FEMALE)
PHYSICAL	
Color	White
Number of Displays	1
Shipping Dimensions (hwd / in.)	6.14 x 4.80 x 1.30
Shipping Dimensions (hwd / cm)	15.60 x 12.19 x 3.30
Shipping Weight (lbs.)	0.37
Shipping Weight (kg)	0.17
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000
COMMUNICATIONS	
Max 1024 x 768 Range (ft)	300
Max 480P Range (ft)	300
Max 1440 x 900 Range (ft)	150
Max 480i Range (ft)	300
Max 640 x 480 Range (ft)	300
Max 800 x 600 Range (ft)	300
EDID Compatible	No
IR Remote Extension Support	No
RS-232 Serial Extension Support	No

Consumer Electronics Control (CEC) Supported	No
USB Extension Support	No
FEATURES & SPECIFICATIONS	
10/100 Ethernet Extension Support	No
Built-In Equalizer	No
Driver Required	No
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	1-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.