

SCALANCE XR108-2PoE WG; unmanaged IE Switch; 19" rack; 8 x 1GE electrical PoE ports; 2 x SFP 10GE port; LED diagnostics power supply 240 V AC (85 – 264 V).



product type designation	SCALANCE XR108-2PoE WG
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10 Gbit/s
interfaces / for communication / integrated	
number of electrical connections	
<ul style="list-style-type: none"> for network components or terminal equipment 	8; RJ45
<ul style="list-style-type: none"> for Power-over-Ethernet / for network components or terminal equipment 	8
number of optical interfaces / for network components or terminal equipment	2
number of 10/100/1000 Mbit/s RJ45 ports / integrated	
<ul style="list-style-type: none"> with PoE 	8
number of electrical connections	
<ul style="list-style-type: none"> for SFP+ 	2
interfaces / other	
number of electrical connections	
<ul style="list-style-type: none"> for power supply 	1
type of electrical connection	
<ul style="list-style-type: none"> for power supply 	IEC plug C14
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage supply / redundant power supply unit	No
supplied active power / of PSE / with PoE	
<ul style="list-style-type: none"> per port / maximum 	60 W
<ul style="list-style-type: none"> total / maximum 	200 W
type of voltage / 1 / of the supply voltage	
<ul style="list-style-type: none"> supply voltage / 1 / rated value 	240 V
<ul style="list-style-type: none"> supply voltage / 1 / rated value 	85 ... 264 V
<ul style="list-style-type: none"> consumed current / 1 / maximum 	4 A
<ul style="list-style-type: none"> product component / 1 / fusing at power supply input 	Yes
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation 	0 ... 60 °C
<ul style="list-style-type: none"> during storage 	-40 ... +85 °C
<ul style="list-style-type: none"> during transport 	-40 ... +85 °C
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP30

design, dimensions and weights	
design	19" rack
number of modular height units / relating to 19-inch cabinet	1
width	482.6 mm
height	43.6 mm
depth	133 mm
net weight	2.9 kg
material / of the enclosure	metal
fastening method	
• 19-inch installation	Yes
• 35 mm top hat DIN rail mounting	No
• wall mounting	No
• S7-300 rail mounting	No
• S7-1500 rail mounting	No
product features, product functions, product components / general	
cascading in cases of star topology	any (depending only on signal propagation time)
product functions / management, configuration, engineering	
product function	
• multiport mirroring	No
• CoS	Yes
product function / switch-managed	No
product functions / redundancy	
product function	
• Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
standards, specifications, approvals	
standard	
• for safety / from CSA and UL	UL 62368-1, CSA C22.2 No. 62368-1
• for emitted interference	EN 61000-6-4
• for interference immunity	EN 61000-6-2
MTBF	47 y
reference code	
• according to IEC 81346-2	KF
• according to IEC 81346-2:2019	KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / other	
certificate of suitability	
• C-Tick	Yes
• KC approval	Yes
• railway application in accordance with EN 50155	No
• EAC approval	Yes
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For

the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>.
(V3.4)

last modified:

7/8/2022 