

# USB-C to USB-A Cable (M/M), Right-Angle C, USB 3.2 Gen 1 (5 Gbps), Thunderbolt 3 Compatible, 3 ft. (0.91 m)

MODEL NUMBER: U428-003-CRA



USB-C to USB-A cable connects a smartphone or other USB-C device to the USB-A port on your computer, wall charger or car charger.

## Features

**USB Type-C to USB Type-A Cable Connects a USB-C Mobile Device to Your Computer** This USB Type-C to Type-A cable allows you to connect a device with a USB-C or Thunderbolt 3 port to a USB-enabled computer, charger, hard drive or other peripheral for the purpose of charging, powering, syncing or transferring data. It is compatible with any device with a USB-C or Thunderbolt 3 port, including tablets, smartphones, MacBooks, Ultrabooks and Chromebooks. The three-foot cord is perfectly suited for use with charging stations and carts.

**Transfers Data and Charges Devices at Fast USB 3.1 Gen 1 Speeds** The USB Type-C to USB-A cable supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps, which is 10 times faster than USB 2.0. It also provides power output up to 3 amps (60 watts), which is sufficient for fast-charging, syncing and powering most devices. The cable is backward compatible with previous USB generations, allowing you to use it with older equipment.

**Reversible USB-C Connector Attaches in Either Direction** Unlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time.

**Right-Angle USB-C Plug Makes Connecting in Tight Spaces Easier** The space-saving right-angle USB-C plug is easy to install in confined spaces, such as behind your computer desk or workstation. The right-angle construction also relieves strain on the cable and connector and prevents the cable from bending awkwardly.

## Specifications

| OVERVIEW   |                      |
|------------|----------------------|
| UPC Code   | 037332214140         |
| Technology | Thunderbolt; USB 3.x |

## Highlights

- Right-angle USB-C plug permits easier connection in confined or hard-to-reach spaces
- Supports USB 3.1 Gen 1 speeds up to 5 Gbps to ensure fast data transfers
- Provides 3A (60W) power output for charging, syncing and powering mobile devices
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- USB-C to USB-A cable compatible with all USB-A, USB-C and Thunderbolt 3 devices

## Applications

- Charge and sync a USB-C mobile device from a USB-A wall charger or charging station
- Connect a printer or scanner to a desktop computer's hard-to-reach rear USB-C port
- Transfer data between an external hard drive or flash drive and your computer or laptop

## System Requirements

- Device with a USB-C or Thunderbolt 3 port (USB 3.1 Gen 1 compatibility required to achieve USB 3.1 Gen 1 speeds)
- Device with a USB-A port

## Package Includes

- U428-003-CRA Right-Angle USB-C to USB-A Cable, M/M, 3 ft.



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| Cable Type                           | Passive                             |
| <b>CONNECTIONS</b>                   |                                     |
| Side A - Connector 1                 | USB C (MALE) - RIGHT ANGLE          |
| Side B - Connector 1                 | USB 3.0 A (MALE)                    |
| Connector Plating                    | Nickel                              |
| Contact Plating                      | Gold                                |
| Connector Style                      | Angled                              |
| <b>PHYSICAL</b>                      |                                     |
| Material of Construction             | PVC                                 |
| Cable Jacket Color                   | Black                               |
| Cable Jacket Rating                  | VW-1                                |
| Cable Outer Diameter (OD)            | 4.5 mm                              |
| Cable Length (ft.)                   | 3                                   |
| Cable Length (m)                     | 0.91                                |
| Cable Length (in.)                   | 36                                  |
| Shipping Dimensions (hwd / in.)      | 9.00 x 7.00 x 0.50                  |
| Shipping Dimensions (hwd / cm)       | 22.86 x 17.78 x 1.27                |
| Shipping Weight (lbs.)               | 0.07                                |
| Shipping Weight (kg)                 | 0.03                                |
| Unit Packaging Type                  | Polybag                             |
| <b>ENVIRONMENTAL</b>                 |                                     |
| Operating Temperature Range          | 32° to 113°F (0° to 45°C)           |
| Storage Temperature Range            | -40° to 158°F (-40° to 70°C)        |
| Operating Humidity Range             | 10% to 85% RH, Non-Condensing       |
| Storage Humidity Range               | 5% to 90% RH, Non-Condensing        |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                     |
| USB Specification                    | USB 3.1 Gen 1 (up to 5 Gbps)        |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                     |
| Product Compliance                   | RoHS; CE (Europe); REACH; FCC (USA) |
| <b>WARRANTY &amp; SUPPORT</b>        |                                     |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty           |



*Powering Business Worldwide*

TRIPP LITE  
SERIES

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.