

# USB 3.2 Gen 2 Active Extension Cable - USB-C to USB-A (M/F), 10 Gbps, Data Only, 5 m (16.4 ft.)

MODEL NUMBER: U330-05M-C2A-G2



Active 16 ft. extension cord increases the distance between two USB devices, including MacBooks and Windows laptops, without signal loss.

## Features

### USB Extension Cable Connects Computers, Printers, Modems and Other USB Equipment

This USB-C to USB-A Active Extension Cable (M/F) attaches to your current USB 3.2 Gen 2 cable to extend it by five meters (16.4 feet). It connects your MacBook Pro, Windows laptop, Chromebook or other compatible USB-C device to a USB-A webcam, keyboard, printer, portable hard drive, patch panel or other peripheral. The extra length allows you greater flexibility in placing equipment where most needed.

### Built-In Signal Booster for Peak Performance

Just connect the active cable's USB-C plug to your computer's USB-C port and the USB-A female connector to a USB device cable to extend your total connection beyond USB's natural five-meter limit. The bus-powered signal booster ensures USB 3.2 Gen 2 data transfer speeds up to 10 Gbps, twice as fast as USB 3.2 Gen 1, with no signal loss. The cable is backward compatible with previous USB generations, so you can use it with legacy equipment.

### 900mA of Proper Power to Keep Devices Functioning

The U330-05M-C2A-G2 works with standard USB 3.2 Gen 2 cables and provides up to 900mA of power to a connected device.

## Specifications

| OVERVIEW    |              |
|-------------|--------------|
| UPC Code    | 037332268686 |
| Technology  | USB 3.x      |
| Cable Type  | Active       |
| INPUT       |              |
| Bus Powered | Yes          |

## Highlights

- Adds 5 meters to your existing USB connection to provide flexibility in placing devices
- Connects existing USB-A peripherals to newer laptops or tablets with USB-C ports
- Supports USB 3.2 Gen 2 speeds up to 10 Gbps to ensure fast data transfers
- Provides up to 900mA of power to connected device without need for external power
- Plug-and-play operation with no software required for easy, immediate installation

## System Requirements

USB 3.2 Gen 2 computer port and USB 3.2 Gen 2 connected device required to meet USB 3.2 Gen 2 speeds

## Package Includes

U330-05M-C2A-G2 USB-C Active Extension Cable, USB-C to USB-A (M/F), 5 m (16.4 ft.)



Powering Business Worldwide

TRIPP LITE  
SERIES

| POWER                                    |                                     |
|------------------------------------------|-------------------------------------|
| USB Power Delivery (PD) Charging Support | No                                  |
| CONNECTIONS                              |                                     |
| Side A - Connector 1                     | USB C (MALE)                        |
| Side B - Connector 1                     | USB A (FEMALE)                      |
| Connector Plating                        | Nickel                              |
| Contact Plating                          | Gold; Nickel                        |
| Connector Style                          | Straight                            |
| PHYSICAL                                 |                                     |
| Material of Construction                 | TPE + ABS                           |
| Cable Jacket Color                       | Black                               |
| Cable Jacket Material                    | TPE                                 |
| Cable Outer Diameter (OD)                | 4.8MM                               |
| Cable Length (ft.)                       | 16.4                                |
| Cable Length (m)                         | 5.00                                |
| Unit Packaging Type                      | Polybag                             |
| Unit Weight (lbs.)                       | 0.51                                |
| Unit Weight (kg)                         | 0.23                                |
| ENVIRONMENTAL                            |                                     |
| Operating Temperature Range              | 32° to 113°F (0° to 45°C)           |
| Storage Temperature Range                | 14° to 158°F (-10° to 70°C)         |
| Operating Humidity Range                 | 10% TO 85% RH, Non-Condensing       |
| Storage Humidity Range                   | 5% TO 90% RH, Non-Condensing        |
| Power Provided to Connected Device(s)    | 900mA                               |
| FEATURES & SPECIFICATIONS                |                                     |
| USB Specification                        | USB 3.2 Gen 2 (Up to 10 Gbps)       |
| Driver Required                          | No                                  |
| STANDARDS & COMPLIANCE                   |                                     |
| Product Compliance                       | RoHS; CE (Europe); REACH; FCC (USA) |
| WARRANTY & SUPPORT                       |                                     |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                        |                         |
|----------------------------------------|-------------------------|
| Product Warranty Period<br>(Worldwide) | 3-year limited warranty |
|----------------------------------------|-------------------------|

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.