

[Turbo Series](#)

TMB-V86-201-S(S)



More Information

 [UL Recognized](#)
 RoHS Compliant

Specifications

Mounting	Panel Mount with Volume Control
Operating Mode	Medium Loud Slow Beep Tone
Operating Voltage	30-120 Vac
Operating Frequency	2900±250 Hz
Typical Operating Current	2 mA at 30 Vac 15 mA at 120 Vac
Typical Sound Pressure	75 ±5 dB(A) at 30 Vac at 24 inches (61 cm), at 25°C 95 ±5 dB(A) at 120 Vac at 24 inches (61 cm), at 25°C
Termination	Quick Connect Blades with Screws
Termination Strength	Pull test with a maximum of 22 pounds (10 kg) load
Operating Temperature	-20_C to +65_C
Storage Temperature	-40_C to +85_C
Surge Voltage	20% over maximum rated voltage for less than 5 minutes
Reverse Voltage Protection	To the maximum operating voltage
Construction Materials	Case- Plastic _NORYL_ N-190, Flame Retardant UL 94-VO, Black Internal Circuit- Audio-oscillator and piezoelectric driver Potting- 2 parts epoxy resin or silicone, black Diaphragm- Stainless Steel 308
Gasket	Gasket (Included) 0.125" thick, 60 Durometer Neoprene
Construction Materials	ASTM B117 Certified - Withstands exposure to salt spray for 300 hours IP 68 Certified - Withstands water submergence and dust exposure Humidity- 95% relative humidity at +40_C continuously for 100 hours. Vibration- Withstands vibration between 0 and 55 Hz. on all axes.
Life Expectancy	10 years under normal operating conditions.
Warranty	For a period of two years from the date of manufacture under normal operating conditions.
Notes	This product is not intended as a life safety device.
Terms and Conditions of Sale	Link here

Diagram of a ring with dimensions: 0.31 in [7.9 mm] and 128 in [32.5 mm].

GASKET



SIDE

0.49 in
[12.4 mm]

122 in
[310 mm]

106 in
[268 mm]

FRONT

141in
[359mm]

PANEL MOUNTING

1065in
[27.051mm]

**FITS PANELS UP TO
0.50in [12.7mm] THICK**

"S" TERMINALS

STAINLESS STEEL SCREWS,
6 X 32 (8.25) LONG (5.4)

0.032 (0.81)

0.312 (7.9)

0.312 (7.9)

0.250 (6.4)

0.188 (4)

5/32 THREAD

"S" TERMINALS

STAINLESS STEEL SCREWS,
6 X 32, 0.25 LONG
(0.4)

FITS PANELS UP TO
0.50in (12.7mm) THICK