

Specification Sheet

Part Number: 151-01033

HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications.

Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.



An assortment of Connector Clips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

Connector Clip w/Oval Fir Tree, 0.6 - 3.0 mm Panel, 6.2 - 13.0mm Hole, PA66HIRHSUV, Black, 1000/ctn

Article Number 151-01033

Type CCOVAL6

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Connector Clip w/Oval Fir Tree, 0.6 - 3.0 mm Panel, 6.2 - 13.0mm Hole, PA66HIRHSUV, Black, 1000/ctn

Global Part Name

CCOVAL6-PA66HIRHSUV-BK

Length L (Imperial)

1.16

Length L (Metric)

29.34

Fixation Method

Fir Tree for oval holes

Variant

6.2 x 12.2 mm 6.5 x 12.5 mm 6.5 x 13.0 mm 7.0 x 12.0 mm

Width W (Imperial)

0.69

Width W (Metric)

17.6

Height H (Imperial)

0.60

Height H (Metric)

15.2

Panel Thickness Min (Imperial)

0.02

Panel Thickness Max (Imperial)

0.12

Panel Thickness Min (Metric)

0.6

Panel Thickness Max (Metric)

3.0

Mounting Hole Diameter D (Imperial)

0.24 x 0.48 " 0.26 x 0.50 " 0.26 x 0.51 " 0.28 x 0.47

Mounting Hole Diameter D (Metric)

6.5 x 12.5 mm 6.5 x 13.0 mm 6.2 x 12.2 mm 7.0 x 12.0 mm

Mounting Hole Diameter D Min (Imperial)

0.24

Mounting Hole Diameter D Max (Imperial)	0.24
Mounting Hole Diameter D Max (Metric)	6.2
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)