

Specification Sheet

Part Number: 151-00775

HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications.

Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.

An assortment of Connector Clips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.



Connector Clip with Round Arrowhead, 1.7-2.3 mm Panel Thick., 6.3-6.7 mm Hole Dia, PA66HIRHS, Black, 5000/box

Article Number 151-00775

Type CCSFT6.5

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton connector clips for oval holes are mounted simply by pushing them onto the corresponding clip. The clips provide a wide range of mounting options with anti-rattle and anti-rotation features. The arrowhead locks firmly into place when inserted into the hole palpably and ensures a secure attachment at all times.

Short Description Connector Clip with Round Arrowhead, 1.7-2.3 mm Panel Thick., 6.3-6.7 mm Hole Dia, PA66HIRHS, Black, 5000/box

Global Part Name

CCSFT6.5-PA66HIRHS-BK

Length L (Imperial)

0.9

Length L (Metric)

23.0

Fixation Method

Arrowhead

Width W (Metric)

16.1

Height H (Imperial)

0.48

Height H (Metric)

12.1

Panel Thickness Min (Imperial)

0.07

Panel Thickness Max (Imperial)

0.09

Panel Thickness Min (Metric)

1.7

Panel Thickness Max (Metric)

2.3

Mounting Hole Diameter D (Imperial)

0.25 - 0.26

Mounting Hole Diameter D (Metric)

6.3 - 6.7 mm

Mounting Hole Diameter D Min (Imperial)

0.25

Mounting Hole Diameter D Max (Imperial)

0.26

Mounting Hole Diameter D Max (Metric)

6.7

Disc Diameter (Metric)	16.0
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	3926909988

