

## Specification Sheet

Part Number: 151-02459

Connector clip design to meet USCAR EWCAP-005-11 clip slot specifications.

Meets installation and extraction requirements of SAE/USCAR-2.



Versatile and robust fir tree design provides low insertion effort yet delivers exceptional retention strength in a 5mm hole and M6 threaded hole.

USCAR Connector Clip with Round Fir Tree, 11mm, 5.0 mm Dia and M6 Threaded Hole, PA66HIRHSUV, Black, 5000/ctn

Article Number 151-02459

Type CC11FTM6

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description USCAR Connector Clip with Round Fir Tree, 11mm, 5.0 mm Dia and M6 Threaded Hole, PA66HIRHSUV, Black, 5000/ctn

Global Part Name CC11FTM6-PA66HIRHSUV-BK

Length L (Imperial) 0.98

Length L (Metric) 24.9

Fixation Method Fir tree for round holes

Variant M6 Threaded Hole

Width W (Imperial) 0.622

Width W (Metric) 15.8

Height H (Imperial) 0.814

Height H (Metric) 20.7

Panel Thickness Min (Imperial) 0.05

Panel Thickness Max (Imperial) 0.18

Panel Thickness Min (Metric) 1.3

Panel Thickness Max (Metric) 4.5

Mounting Hole Diameter D (Imperial) 0.24

Mounting Hole Diameter D (Metric) M6

Mounting Hole Diameter D Min (Imperial) 0.256

Mounting Hole Diameter D Max (Imperial)	0.276
Mounting Hole Diameter D Max (Metric)	7.0
Disc Diameter (Metric)	17.5
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	5008
Package Quantity (Metric)	5000
Customs Number	3926909988

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)