

Specification Sheet

Part Number: 157-00069

All-in-one bundling and fastening solution reduces costs and assembly time.

Anti-rotational oval fastener forces bundle to travel in intended direction.

High-spec materials and superior design deliver excellent performance and value.



1-Piece Cable Tie/Oval Fir Tree Mount/Disc, 6.5"L, 6.2 x 12.2 mm Mounting Hole, PA46, Gray, 1000/bg

Article Number 157-00069

Type T50SOS2DOP62X122-E

Color Gray (GY)

Quantity Per bag

Product Description One-piece cable tie and mount offers a simple bundling and mounting solution. The innovative design of this fir tree establishes a 360-degree interface with the panel hole, ensuring a more secure fit. The oval shape won't rotate once inserted, ensuring proper routing of wires and hoses. The disc feature prevents rattling in high-vibration applications and protects against debris ingress.

Short Description 1-Piece Cable Tie/Oval Fir Tree Mount/Disc, 6.5"L, 6.2 x 12.2 mm Mounting Hole, PA46, Gray, 1000/bg

Global Part Name T50SOS2DOP62X122-E-PA46-GY

Minimum Tensile Strength (Imperial) 45

Minimum Tensile Strength (Metric) 200

Length L (Imperial) 6.5

Length L (Metric) 164.0

Fixation Method Fir tree for round holes

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.04

Bundle Diameter Min (Metric) 1.0

Bundle Diameter Max (Imperial) 1.38

Bundle Diameter Max (Metric) 35.0

Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3
Height H (Imperial)	0.41
Height H (Metric)	10.5
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.24
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.24 x 0.48
Mounting Hole Diameter D (Metric)	6.2 x 12.2 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.48
Mounting Hole Diameter D Max (Metric)	12.2
Disc Diameter (Metric)	16.0 x 21.0
Disc Diameter (Imperial)	0.63 x 0.83

Material	Polyamide 4.6 (PA46)
Material Shortcut	PA46
Material Cable Tie	Polyamide 4.6 (PA46)
Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +275°F (-40°C to +135°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988