

## Specification Sheet

Part Number: 126-00065



Design helps silence and stabilize the tie in high-vibration applications.

Arrowhead-style mount provides low insertion and high extraction force.

Rubber seal restricts water and debris from passing through mounting hole.

1-Piece Cable Tie/Arrowhead Mount with Seal, 6.5" Long, 50lb Tensile, PA66HS, Natural, 500/bg

Article Number

126-00065

Type

T50SOSSFT6.5E-MS-MD

Color

Natural (NA)

Quantity Per

bag

Product Description

The arrowhead design of these ties offers a positive, low insertion force and a high extraction force. These ties feature a foam rubber seal which provides additional protection against moisture, dirt, and other impurities. One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description

1-Piece Cable Tie/Arrowhead Mount with Seal, 6.5" Long, 50lb Tensile, PA66HS, Natural, 500/bg

Global Part Name T50SOSSFT6.5E-MS-MD-PA66HS-NA

Minimum Tensile Strength (Imperial) 40

Minimum Tensile Strength (Metric) 180

Length L (Imperial) 6.5

Length L (Metric) 163.0

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.5

Bundle Diameter Max (Imperial) 1.38

Bundle Diameter Max (Metric) 35.0

Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3
Height H (Imperial)	0.63
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.06
Panel Thickness Min (Metric)	0.7
Panel Thickness Max (Metric)	1.6
Mounting Hole Diameter D (Imperial)	0.24 - 0.26 (hexagonal) ";0.25 - 0.27
Mounting Hole Diameter D (Metric)	6.1 - 6.6 mm (hexagonal) 6.25 - 6.75 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.27
Mounting Hole Diameter D Max (Metric)	6.75
Disc Diameter (Metric)	16.0
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut	PA66HS
Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988