

Specification Sheet

Part Number: 156-00870

Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.

Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

Two piece assembly allows the mount to slide along the strap ensuring proper orientation.

Cable tie is outside serrated to reduce bundle chafing.



Outside Serrated Cable Tie & Edge Clip, 6.0" Long, EC10, 1 - 3 mm Panel, 50lb, PA66HS, Black, 500/pkg

Article Number 156-00870

Type T50SOSEC10

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place.

| | |
|-------------------------------------|---|
| Short Description | Outside Serrated Cable Tie & Edge Clip, 6.0" Long, EC10, 1 - 3 mm Panel, 50lb, PA66HS, Black, 500/pkg |
| Global Part Name | T50SOSEC10-PA66HS/PA66HIRHS-BK |
| Minimum Tensile Strength (Imperial) | 50 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 150 |
| Fixation Method | Edge Clip |
| Identification Plate Position | none |
| Variant | Outside Serrated |
| Width W (Imperial) | 0.18 |
| Width W (Metric) | 4.6 |
| Bundle Diameter Min (Imperial) | 0.04 |
| Bundle Diameter Min (Metric) | 1.0 |
| Bundle Diameter Max (Imperial) | 1.22 |
| Bundle Diameter Max (Metric) | 31.0 |
| Thickness T (Imperial) | 0.05 |

| | |
|--------------------------------|---|
| Height H (Imperial) | 0.05 |
| Height H (Metric) | 1.3 |
| Panel Thickness Min (Imperial) | 0.04 |
| Panel Thickness Max (Imperial) | 0.12 |
| Panel Thickness Min (Metric) | 1.0 |
| Panel Thickness Max (Metric) | 3.0 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Foot Part Material | PA66HIRHS |
| Material Shortcut | PA66HS PA66HIRHS |
| Material Cable Tie | Polyamide 6.6 heat stabilized (PA66HS) |
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | No |

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988