

## Specification Sheet

Part Number: 126-00044

All-in-one bundling and fastening solution reduces costs and assembly time.

The arrowhead design of these ties offers a low insertion force and a high extraction force.

High-spec materials and superior design deliver versatility, performance and value.



1-Piece Cable Tie/Arrowhead Mount, 6"L, 50lb, 0.04 - 0.14" Panel Thickness, PA66, Natural, 1000/pkg

Article Number 126-00044

Type T50SSF

Color Natural (NA)

Quantity Per bag

Product Description One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. The arrowhead design of this push mount inserts easily and locks securely in place. HellermannTyton's one-piece mounting ties combine high-specification materials with superior design to deliver dependable performance in a range of applications.

Short Description 1-Piece Cable Tie/Arrowhead Mount, 6"L, 50lb, 0.04 - 0.14" Panel Thickness, PA66, Natural, 1000/pkg

Global Part Name T50SSF-PA66-NA

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 6.25

Length L (Metric) 159.0

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19

Width W (Metric) 4.7

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.5

Bundle Diameter Max (Imperial) 1.38

Bundle Diameter Max (Metric) 35.0

|   |              |
|---|--------------|
| Height H (Imperial)                     | .30          |
| Height H (Metric)                       | 7.50         |
| Panel Thickness Min (Imperial)          | 0.04         |
| Panel Thickness Max (Imperial)          | 0.14         |
| Panel Thickness Min (Metric)            | 1.0          |
| Panel Thickness Max (Metric)            | 3.56         |
| Mounting Hole Diameter D (Imperial)     | 0.25 - 0.28  |
| Mounting Hole Diameter D (Metric)       | 6.4 - 7.1 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.25         |
| Mounting Hole Diameter D Max (Imperial) | 0.28         |
| Mounting Hole Diameter D Max (Metric)   | 7.1          |

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL 94 V-2

UV Resistant (Yes/No) No

|                               |                                  |
|-------------------------------|----------------------------------|
| Use Conditions                | For Indoor Use Only              |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33)  | No                               |
| ROHS Compliant                | Yes                              |
| UL Recognized (US)            | Yes                              |
| UL Recognized (US and Canada) | Yes                              |
| Package Quantity (Imperial)   | 1000                             |
| Package Quantity (Metric)     | 1000                             |
| Customs Number                | 3926909988                       |

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)