

Specification Sheet

Part Number: 111-85850



An all-in-one bundling and fixing solution reduces costs.

Disc provides secure insertion and minimizes access of dust, dirt and water.

1-Piece Cable Tie/Arrowhead Mount, 8.9"L, 50lb, Mounting Hole Dia. 0.27 - 0.28", PA66HS, Black, 100/pkg

Article Number 111-85850

Type T50MD7

Color Black (BK)

Quantity Per pcs.

Product Description The Domed Push Mount Tie provides a tight, rattle-free installation and acts as a seal to keep out dust and debris. One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution.

Short Description 1-Piece Cable Tie/Arrowhead Mount, 8.9"L, 50lb, Mounting Hole Dia. 0.27 - 0.28", PA66HS, Black, 100/pkg

Global Part Name T50MD7-PA66HS-BK

| | |
|-------------------------------------|-----------------|
| Minimum Tensile Strength (Imperial) | 50 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 9.0 |
| Length L (Metric) | 225.0 |
| Fixation Method | Arrowhead |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.20 |
| Width W (Metric) | 5.0 |
| Bundle Diameter Min (Imperial) | 0.39 |
| Bundle Diameter Min (Metric) | 10.0 |
| Bundle Diameter Max (Imperial) | 2.32 |
| Bundle Diameter Max (Metric) | 59.0 |
| Thickness T (Imperial) | 0.06 |

| | |
|---|--|
| Thickness T (Metric) | 1.5 |
| Panel Thickness Min (Imperial) | 0.03 |
| Panel Thickness Max (Imperial) | 0.08 |
| Panel Thickness Min (Metric) | 1.2 |
| Panel Thickness Max (Metric) | 2.0 |
| Mounting Hole Diameter D (Imperial) | 0.27 - 0.28 |
| Mounting Hole Diameter D (Metric) | 6.8 - 7.2 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.27 |
| Mounting Hole Diameter D Max (Imperial) | 0.28 |
| Mounting Hole Diameter D Max (Metric) | 7.2 |
| Disc Diameter (Metric) | 16.0 |
| Disc Diameter (Imperial) | 0.63 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V-2 |

| | |
|------------------------------|-----------------------------------|
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)