

Specification Sheet

Part Number: T150M0HSX2



Heat stabilized heavy duty cable ties provide excellent resistance to high heat exposures.

Head design provides high tensile strength with very low insertion force

Heavy Duty Cable Tie, 21" Long, UL Rated, 175lb Tensile Strength, PA66HS, Black, 25/pkg

Article Number 111-15609

Type T150M

Color Black (BK)

Quantity Per bag

Product Description Heavy duty T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Heavy Duty Cable Tie, 21" Long, UL Rated, 175lb Tensile Strength, PA66HS, Black, 25/pkg

Global Part Name T150M-PA66HS-BK

| | |
|-------------------------------------|-----------------|
| Minimum Tensile Strength (Imperial) | 175 |
| Minimum Tensile Strength (Metric) | 780 |
| Length L (Imperial) | 21.0 |
| Length L (Metric) | 530.0 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.35 |
| Width W (Metric) | 8.9 |
| Bundle Diameter Min (Imperial) | 0.31 |
| Bundle Diameter Min (Metric) | 8.0 |
| Bundle Diameter Max (Imperial) | 5.91 |
| Bundle Diameter Max (Metric) | 150.0 |
| Thickness T (Imperial) | 0.079 |
| Thickness T (Metric) | 2 |

| | |
|-------------------------------|--|
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V-2 |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor and Outdoor Use |
| Plenum Rating | AH-2 |
| Operating Temperature | -40°F to +257°F (-40°C to +125°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | UL 62275 |
| UL Recognized (US) | Yes |
| UL Listed (US and Canada) | Yes |
| UL Recognized (US and Canada) | Yes |
| UL Listed (US) | Yes |

Package Quantity (Imperial) 25

Package Quantity (Metric) 25

Customs Number 3926909988