

## Specification Sheet

Part Number: 156-04007

Robust fir tree design provides low insertion effort yet delivers exceptional retention strength.

Anti-rotational oval fir tree keeps bundle in intended direction.

Heavy duty T120 tie provides 120 lb (534 N) tensile strength to secure bundles up to 4" (104 mm).

Friction tab inside fir tree allows the tie to sit in mount without falling out prior to installation.



3-Piece Cable Tie/Oval Fir Tree Mount, Unassembled Set, 15"L, 12x17mm Hole, PA66HIRHSUV, Black, 500/ctn

|                     |   |
|---------------------|---|
| Article Number      | 156-04007   |
| Type                | T120R2xDHVSDL12x17  |
| Color               | Black (BK)  |
| Quantity Per        | carton  |
| Product Description | HellermannTyton's Fir Tree Mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. They are optimized for up to 3-to-1 extraction versus insertion force to make assembly fast and easy. These mounts are sold unassembled. |

|                                     |   |
|-------------------------------------|---|
| Short Description                   | 3-Piece Cable Tie/Oval Fir Tree Mount, Unassembled Set, 15"L, 12x17mm Hole, PA66HIRHSUV, Black, 500/ctn |
| Global Part Name                    | T120R2xDHVSDL12x17-PA66HIRHSUV-BK   |
| Minimum Tensile Strength (Imperial) | 120   |
| Minimum Tensile Strength (Metric)   | 535   |
| Length L (Imperial)                 | 8.0   |
| Length L (Metric)                   | 203.2   |
| Fixation Method                     | Fir tree for round holes  |
| Identification Plate Position       | none  |
| Releasable Closure                  | No  |
| Tie Closure                         | plastic pawl  |
| Variant                             | Inside Serrated   |
| Width W (Imperial)                  | 0.30  |
| Width W (Metric)                    | 7.6   |
| Bundle Diameter Min (Imperial)      | 0.2   |
| Bundle Diameter Min (Metric)        | 5.0   |
| Bundle Diameter Max (Imperial)      | 4.13  |

|   |  |
|---|--|
| Bundle Diameter Max (Metric)            | 105.0  |
| Thickness T (Imperial)                  | 0.07   |
| Thickness T (Metric)                    | 1.8  |
| Height H (Imperial)                     | 1.36   |
| Height H (Metric)                       | 34.74  |
| Panel Thickness Min (Imperial)          | 0.02   |
| Panel Thickness Max (Imperial)          | 0.26   |
| Panel Thickness Min (Metric)            | 0.6  |
| Panel Thickness Max (Metric)            | 6.75   |
| Mounting Hole Diameter D (Imperial)     | 0.47 x 0.67  |
| Mounting Hole Diameter D (Metric)       | 12.0 x 17.0 mm   |
| Mounting Hole Diameter D Max (Imperial) | 0.47 x 0.67  |
| Material                                | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Foot Part Material                      | PA66HIRHSUV  |
| Material Shortcut                       | PA66HIRHSUV  |

|                             |  |
|-----------------------------|--|
| Material Cable Tie          | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Flammability                | UL 94 HB   |
| Halogen Free                | Yes  |
| UV Resistant (Yes/No)       | Yes  |
| Use Conditions              | For Indoor and Outdoor Use   |
| Operating Temperature       | -40°F to +221°F (-40°C to +105°C)  |
| ROHS Compliant              | Yes  |
| Package Quantity (Imperial) | 500  |
| Package Quantity (Metric)   | 500  |
| Customs Number              | 3926909988   |

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)