

Specification Sheet

Part Number: T150XL0X2



Engineered and manufactured for maximum performance and quality.

Made from 100% high-quality plastic to ensure efficient recycling.

Inside serration for a strong grip onto bundles.

Easy application either manually or with a tensioning tool.

Heavy Duty Cable Tie, 43" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 25/pkg

Article Number 111-15500

Type T150XL

Color Black (BK)

Quantity Per bag

Product Description Heavy duty T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Heavy Duty Cable Tie, 43" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 25/pkg

Global Part Name T150XL-PA66-BK

Minimum Tensile Strength (Imperial) 175

Minimum Tensile Strength (Metric) 780

Length L (Imperial) 43.0

Length L (Metric) 1095.0

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.35

Width W (Metric) 8.9

Bundle Diameter Min (Imperial) 5.98

Bundle Diameter Min (Metric) 152.0

Bundle Diameter Max (Imperial) 12.99

Bundle Diameter Max (Metric) 330.0

Thickness T (Imperial) 0.083

Thickness T (Metric)	2.1
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL ANSI/UL 62275 UL ANSI/UL 1565 UL ANSI/UL 746B
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	25
Package Quantity (Metric)	25

Customs Number

3926909988

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)