


## Specification Sheet

Part Number: 170-23000



Nylon monofilament construction weave offers a tight braid that provides full coverage but will not rot or retain moisture.

Material performs well in wet applications and where abiding substrate has a smooth surface.

Helagaine Braided Sleeving, 30 mm Dia, PA66, GY, 164ft/Reel

Article Number 170-23000

Type HEGPA6630

Color Gray (GY)

Quantity Per metre

Product Description Helagaine Nylon Polyamide Expandable Braided Sleeving is a pliable yet durable sleeve that protects against cuts, abrasion and excessive wear caused by repetitive motion.

Short Description Helagaine Braided Sleeving, 30 mm Dia, PA66, GY, 164ft/Reel

Global Part Name HEGPA6630-PA66-GY

Length L (Imperial)	164.0
Length L (Metric)	50.0
Bundle Diameter Min (Imperial)	0.98
Bundle Diameter Min (Metric)	25
Bundle Diameter Max (Imperial)	1.26
Bundle Diameter Max (Metric)	32
Diameter D (Imperial)	1.18
Diameter D (Metric)	29.9
Nominal Diameter (Imperial)	1.25
Nominal Diameter (Metric)	30
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	FMVSS 302 UL 94 V-2
Halogen Free	Yes
UV Resistant (Yes/No)	No

Use Conditions	For Indoor Use Only
Operating Temperature	-76°F to +302°F (-60°C to +150°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	164.0
Package Quantity (Metric)	50
Customs Number	5808100000

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)