

## Specification Sheet

Part Number: 184-33014

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High Density Slotted Wall Wiring Duct, 3" x 3", Non-Adhesive, PVC, Black, 30ft/Box

Article Number 184-33014

Type SLHD3X3

Color Black (BK)

Quantity Per box

Product Description HellermannTyton High-Density Slotted Wall Wiring Duct features narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

|                                  |  |
|----------------------------------|--|
| Short Description                | High Density Slotted Wall Wiring Duct, 3" x 3", Non-Adhesive, PVC, Black, 30ft/Box |
| Global Part Name                 | SLHD3X3-PVC-BK   |
| Length L (Imperial)              | 6.0  |
| Length L (Metric)                | 1.83   |
| Width W (Imperial)               | 3.0  |
| Width W (Metric)                 | 76.2   |
| Height H (Imperial)              | 3.07   |
| Height H (Metric)                | 77.9   |
| Mounting Hole Centers (Imperial) | 2.0  |
| Material                         | Polyvinylchloride (PVC)  |
| Material Shortcut                | PVC  |
| Halogen Free                     | No   |
| UV Resistant (Yes/No)            | No   |
| Use Conditions                   | For Indoor Use Only  |

|                              |  |
|------------------------------|--|
| Operating Temperature        | +122°F (+50°C)                                   |
| Reach Compliant (Article 33) | No   |
| ROHS Compliant               | Yes  |
| Certification/Specification  | UL CSA EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A |
| UL Recognized (US)           | Yes  |
| Package Quantity (Imperial)  | 30.0   |
| Package Quantity (Metric)    | 9.14   |
| Customs Number               | 3925900000                                       |

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)