



Circuit breaker size S2 for motor protection, CLASS 10 A-release 28...36 A  
N-release 520 A screw terminal Standard switching capacity

|  |                      |
|--|----------------------|
| <b>product brand name</b>  | SIRIUS               |
| <b>product designation</b>   | Circuit breaker      |
| <b>design of the product</b>   | For motor protection |
| <b>product type designation</b>  | 3RV2                 |
| <b>General technical data</b>  |                      |
| <b>size of the circuit-breaker</b>   | S2                   |
| <b>size of contactor can be combined company-specific</b>                                  | S2                   |
| product extension auxiliary switch   | Yes                  |
| <b>power loss [W] for rated value of the current</b>                                       |                      |
| • at AC in hot operating state   | 20 W                 |
| • at AC in hot operating state per pole  | 6.7 W                |
| insulation voltage with degree of pollution 3 at AC rated value                            | 690 V                |
| <b>surge voltage resistance rated value</b>  | 6 kV                 |
| shock resistance according to IEC 60068-2-27   | 25g / 11 ms Sinus    |
| <b>mechanical service life (switching cycles)</b>  |                      |
| • of the main contacts typical   | 50 000               |
| • of auxiliary contacts typical  | 50 000               |
| electrical endurance (switching cycles) typical  | 50 000               |
| <b>type of protection according to ATEX directive 2014/34/EU</b>                           | Ex II (2) GD         |
| certificate of suitability according to ATEX directive 2014/34/EU                          | DMT 02 ATEX F 001    |
| <b>reference code according to IEC 81346-2</b>   | Q                    |
| <b>Substance Prohibitance (Date)</b>   | 10/15/2014           |
| <b>Ambient conditions</b>  |                      |
| installation altitude at height above sea level maximum                                    | 2 000 m              |
| <b>ambient temperature</b>   |                      |
| • during operation   | -20 ... +60 °C       |
| • during storage   | -50 ... +80 °C       |
| • during transport   | -50 ... +80 °C       |
| relative humidity during operation   | 10 ... 95 %          |
| <b>Main circuit</b>  |                      |
| <b>number of poles for main current circuit</b>  | 3                    |
| <b>adjustable current response value current of the current-dependent overload release</b> | 28 ... 36 A          |
| <b>operating voltage</b>   |                      |
| • rated value  | 20 ... 690 V         |
| • at AC-3 rated value maximum  | 690 V                |
| • at AC-3e rated value maximum   | 690 V                |

|  |               |
|--|---------------|
| <b>operating frequency rated value</b>   | 50 ... 60 Hz  |
| <b>operational current rated value</b>   | 36 A          |
| <b>operational current</b>   |               |
| • at AC-3 at 400 V rated value   | 36 A          |
| • at AC-3e at 400 V rated value  | 36 A          |
| <b>operating power</b>   |               |
| • at AC-3  |               |
| — at 230 V rated value   | 11 kW         |
| — at 400 V rated value   | 18.5 kW       |
| — at 500 V rated value   | 22 kW         |
| — at 690 V rated value   | 30 kW         |
| • at AC-3e   |               |
| — at 230 V rated value   | 11 kW         |
| — at 400 V rated value   | 18.5 kW       |
| — at 500 V rated value   | 22 kW         |
| — at 690 V rated value   | 30 kW         |
| <b>operating frequency</b>   |               |
| • at AC-3 maximum  | 15 1/h        |
| • at AC-3e maximum   | 15 1/h        |
| <b>Protective and monitoring functions</b>   |               |
| <b>product function</b>  |               |
| • ground fault detection   | No            |
| • phase failure detection  | Yes           |
| <b>trip class</b>  | CLASS 10      |
| <b>design of the overload release</b>  | thermal       |
| <b>breaking capacity maximum short-circuit current (Icu)</b>                                   |               |
| • at AC at 240 V rated value   | 100 kA        |
| • at AC at 400 V rated value   | 65 kA         |
| • at AC at 500 V rated value   | 10 kA         |
| • at AC at 690 V rated value   | 4 kA          |
| <b>breaking capacity operating short-circuit current (Ics) at AC</b>                           |               |
| • at 240 V rated value   | 100 kA        |
| • at 400 V rated value   | 30 kA         |
| • at 500 V rated value   | 5 kA          |
| • at 690 V rated value   | 2 kA          |
| response value current of instantaneous short-circuit trip unit                                | 520 A         |
| <b>UL/CSA ratings</b>  |               |
| <b>full-load current (FLA) for 3-phase AC motor</b>  |               |
| • at 480 V rated value   | 36 A          |
| • at 600 V rated value   | 36 A          |
| <b>yielded mechanical performance [hp]</b>   |               |
| • for single-phase AC motor  |               |
| — at 110/120 V rated value   | 3 hp          |
| — at 230 V rated value   | 7.5 hp        |
| • for 3-phase AC motor   |               |
| — at 200/208 V rated value   | 15 hp         |
| — at 220/230 V rated value   | 15 hp         |
| — at 460/480 V rated value   | 30 hp         |
| — at 575/600 V rated value   | 40 hp         |
| <b>Short-circuit protection</b>  |               |
| <b>product function short circuit protection</b>   | Yes           |
| <b>design of the short-circuit trip</b>  | magnetic      |
| <b>design of the fuse link for IT network for short-circuit protection of the main circuit</b> |               |
| • at 240 V   | none required |
| • at 400 V   | 125           |
| • at 500 V   | 100           |
| • at 690 V   | 80            |

| Installation/ mounting/ dimensions   |  |
|--|--|
| <b>mounting position</b>   | any  |
| <b>fastening method</b>  | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715 |
| <b>height</b>  | 140 mm   |
| <b>width</b>   | 55 mm  |
| <b>depth</b>   | 149 mm   |
| <b>required spacing</b>  |  |
| <ul style="list-style-type: none"> <li>● for grounded parts at 400 V <ul style="list-style-type: none"> <li>— downwards 50 mm</li> <li>— upwards 50 mm</li> <li>— at the side 10 mm</li> </ul> </li> <li>● for live parts at 400 V <ul style="list-style-type: none"> <li>— downwards 50 mm</li> <li>— upwards 50 mm</li> <li>— at the side 10 mm</li> </ul> </li> <li>● for grounded parts at 500 V <ul style="list-style-type: none"> <li>— downwards 50 mm</li> <li>— upwards 50 mm</li> <li>— at the side 10 mm</li> </ul> </li> <li>● for live parts at 500 V <ul style="list-style-type: none"> <li>— downwards 50 mm</li> <li>— upwards 50 mm</li> <li>— at the side 10 mm</li> </ul> </li> <li>● for grounded parts at 690 V <ul style="list-style-type: none"> <li>— downwards 50 mm</li> <li>— upwards 50 mm</li> <li>— at the side 10 mm</li> </ul> </li> <li>● for live parts at 690 V <ul style="list-style-type: none"> <li>— downwards 50 mm</li> <li>— upwards 50 mm</li> <li>— at the side 10 mm</li> </ul> </li> </ul> |  |
| Connections/ Terminals   |  |
| <b>type of electrical connection</b>   |  |
| <ul style="list-style-type: none"> <li>● for main current circuit</li> </ul>   | screw-type terminals   |
| <b>arrangement of electrical connectors for main current circuit</b>   | Top and bottom   |
| <b>type of connectable conductor cross-sections</b>  |  |
| <ul style="list-style-type: none"> <li>● for main contacts <ul style="list-style-type: none"> <li>— solid or stranded 2x (1 ... 25 mm<sup>2</sup>), 1x (1 ... 35 mm<sup>2</sup>)</li> <li>— finely stranded with core end processing 2x (1 ... 16 mm<sup>2</sup>), 1x (1 ... 25 mm<sup>2</sup>)</li> </ul> </li> <li>● at AWG cables for main contacts 2x (18 ... 3), 1x (18 ... 2)</li> </ul>   |  |
| <b>tightening torque</b>   |  |
| <ul style="list-style-type: none"> <li>● for main contacts with screw-type terminals</li> </ul>  | 3 ... 4.5 N·m  |
| <b>design of screwdriver shaft</b>   | Diameter 5 to 6 mm   |
| <b>size of the screwdriver tip</b>   | Pozidriv size 2  |
| <b>design of the thread of the connection screw</b>  |  |
| <ul style="list-style-type: none"> <li>● for main contacts</li> </ul>  | M6   |
| Safety related data  |  |
| <b>B10 value</b>   |  |
| <ul style="list-style-type: none"> <li>● with high demand rate according to SN 31920</li> </ul>  | 5 000  |
| <b>proportion of dangerous failures</b>  |  |
| <ul style="list-style-type: none"> <li>● with low demand rate according to SN 31920</li> <li>● with high demand rate according to SN 31920</li> </ul>  | 50 %<br>50 %   |
| <b>failure rate [FIT]</b>  |  |
| <ul style="list-style-type: none"> <li>● with low demand rate according to SN 31920</li> </ul>   | 50 FIT   |
| T1 value for proof test interval or service life according to IEC 61508  | 10 y   |
| <b>protection class IP on the front according to IEC 60529</b>   | IP20   |
| <b>touch protection on the front according to IEC 60529</b>  | finger-safe, for vertical contact from the front                                       |

## Certificates/ approvals

## General Product Approval


[Confirmation](#)


CCC



UL

[KC](#)


## For use in hazardous locations



IECEX



ATEX

## Declaration of Conformity



EG-Konf.

## Test Certificates

[Special Test Certificate](#)
[Type Test Certificates/Test Report](#)

## Marine / Shipping



ABS

BUREAU  
VERITAS

DNV



LRS



PRS



RINA

## Marine / Shipping

## other

## Railway



RMRS

[Confirmation](#)


VDE

[Vibration and Shock](#)
[Confirmation](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV2031-4PA10>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV2031-4PA10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2031-4PA10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RV2031-4PA10&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV2031-4PA10&lang=en)

Characteristic: Tripping characteristics, I<sup>t</sup>, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2031-4PA10/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RV2031-4PA10&objecttype=14&gridview=view1>

last modified:

6/25/2022