


M.2 NGFF SSD (B-Key) to 2.5 in. SATA Open-Frame Housing Adapter

MODEL NUMBER: P960-001-M2-NE



M.2 SSD to SATA adapter increases performance of your 2.5 in. SATA application when connected to an M.2 NGFF SATA SSD drive.

Features

SSD to SATA Adapter Improves Performance of Your SATA Computer This adapter converts your M.2 NGFF SSD drive into a 2.5-inch SATA SSD for use with a standard SATA-enabled computer. The open-frame P960-001-M2-NE supports mount drive heights of 2242, 2260 and 2280, as well as data transfer rates up to 6 Gbps. Adding an M.2 NGFF SSD to your application can reduce your computer's power consumption and boost performance.

Open-Frame Housing Helps Keep the Intricate Electronic Components Cool The open frame is designed for maximum heat dissipation, keeping the adapter cool to boost its performance potential. To share data, simply connect the SATA drive to the M.2 NGFF connector and then the SATA connector to your computer's SATA port.

Just Plug and Play for Immediate Use Right Out of the Package No software, drivers or external power supply is required. Mounting hardware is included. The P960-001-M2-NE is compatible with all major operating systems, including Windows, Mac and Linux.

Highlights

- Connects 2242, 2260 and 2280 M.2 SATA SSD drives to your 2.5 in. SATA application
- Shares data at rapid transfer speeds up to 6 Gbps (SATA I/II/III)
- Open-frame housing provides maximum airflow to keep electronics cool
- Works with all major operating systems, including Windows, Mac and Linux
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Access old data or back up new data on an M.2 NGFF SSD using a SATA-enabled computer

System Requirements

- SATA host device
- B-Key or B+M Key M.2 NGFF SATA drive
- PCIe drives not supported

Package Includes

- P960-001-M2-NE M.2 NGFF SSD to 2.5 in. SATA Open-Frame Housing Adapter
- Mounting hardware
- Screwdriver
- Owner's manual

Specifications

OVERVIEW	
UPC Code	037332242600
Drives Supported	2242, 2260, 2280 M.2 NGFF SSD
Technology	SATA/eSATA
INPUT	
Bus Powered	Yes
CONNECTIONS	



Powering Business Worldwide



Side A - Connector 1	M.2 NGFF SATA (B-Key)
Side B - Connector 1	22 PIN SATA + POWER (FEMALE)
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Yellow (Data & Power)
PHYSICAL	
Color	Green
Shipping Dimensions (hwd / in.)	1.10 x 4.80 x 6.10
Unit Dimensions (hwd / in.)	0.280 x 3.920 x 2.760
Unit Weight (lbs.)	0.11
Unit Weight (kg)	0.05
ENVIRONMENTAL	
Operating Temperature Range	50° to 122°F (10° to 50°C)
Storage Temperature Range	32° to 149°F (0° to 65°C)
Relative Humidity	10% to 80% RH, Non-Condensing
FEATURES & SPECIFICATIONS	
IP68 Rated	No
IP20 Rated	No
Driver Required	No
STANDARDS & COMPLIANCE	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	1-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.