

#### Important Note

This Thunderbolt 3 docking station must be connected to a Thunderbolt 3-enabled laptop or computer using a Thunderbolt 3 cable to achieve maximum data transfer and video transmission specifications. It is important that the host PC allows for administrator access when connecting the dock for the first time in order to allow the automatic driver installation to take place. If this is not an option please see the product's web page on <https://tripplite.eaton.com> to download the drivers manually.

## Thunderbolt 3 Dock w USB-C Compatibility, Dual Display - 8K DisplayPort, USB 3.2 Gen 2 10G, USB-A/C Hub, Memory Card, GbE, 60W Charging

MODEL NUMBER: MTB3-DOCK-03



Turns your MacBook Pro or Windows laptop into a 10-port workstation capable of transmitting 8K video.

#### Features

**Thunderbolt 3 Dock Turns Your MacBook Pro into a 10-Port 8K Workstation** This Thunderbolt 3 docking station dramatically expands the potential of your MacBook Pro or Windows laptop by adding 10 ports to its Thunderbolt 3 or USB-C MFPD port. Not only does the MTB3-DOCK-03 allow you to transmit 8K video to one display or 4K video to two displays, you can also add USB peripherals, record a podcast, connect to a Gigabit Ethernet network, charge your laptop and more, all at the same time.

**Supports DisplayPort Alternate Mode for Transmitting Audio/Video Signals** By connecting the included Thunderbolt 3 cable to a source device that supports DisplayPort Alt Mode, you can output 4K video and digital audio to a compatible monitor, television or projector without installing special software drivers.

**Thunderbolt 3 Supports Blisteringly Fast 40 Gbps Data Transfer Speeds** The included Thunderbolt 3 cable supports bidirectional speeds up to 40 Gbps, which is eight times faster than USB 3.0, four times faster than Thunderbolt 1 and twice as fast as Thunderbolt 2. With dual 20 Gbps channels moving data both directions at the same time, the MTB3-DOCK-03 is perfectly suited for 4K video streaming and editing on two monitors, as well as transferring large RAW video or CAD files. When connected to a host computer's USB-C MFPD port, the cable supports 26.2 Gbps speeds (USB 3.2 Gen 2 10 Gbps + DisplayPort 1.4 8.1G x2 Lane)

**DisplayPort Multi-Stream Transport (MST) Allows Connection of Multiple Displays** By connecting the included Thunderbolt 3 cable to a Thunderbolt source that supports DisplayPort MST Mode, you may connect two displays simultaneously (DP & USB-C) at resolutions of 8K (30 Hz) plus 4K (30 Hz) or both displays at 4K (60 Hz). This allows you to display the same image on both monitors, extend your host desktop across both with different windows open on each, or combine both into one large display as a video wall. Up to three total displays can be utilized if the dock is connected to a compatible laptop (DP +

#### Highlights

- Connects 2 displays at the same time for multitasking and increasing productivity via a Thunderbolt 3-enabled host
- Transmits 8K video (7680 x 4320) @ 30 Hz to a single display for professional users
- Can operate with Thunderbolt 3 or USB-C Multi-Function DisplayPort (MFPD) host
- Supports Thunderbolt 3 speeds up to 40 Gbps between compatible devices
- USB 3.2 Gen 2 data ports allow connection of flash drives and other peripherals

#### Applications

- Extend or mirror your MacBook Pro or Windows laptop on multiple displays to aid in multitasking and increase productivity
- Edit HDR production video or digital photos using an 8K monitor
- Transfer files from one Thunderbolt 3 device to another at 40 Gbps
- Access a wired Gigabit Ethernet network in a location with no or spotty Wi-Fi
- Connect a microphone/headset to record a podcast or speakers to listen to music

#### System Requirements

- Source device with Thunderbolt 3 port that supports DisplayPort MST Mode or USB-C port that supports Multi-Function DisplayPort
- Display device with Thunderbolt 3 or DisplayPort input

#### Package Includes

- MTB3-DOCK-03 Thunderbolt 3 Dock, Dual Display
- Thunderbolt 3 cable (M/M), 1.6 ft.
- External power supply (Input: 100–240V, 50/60 Hz, 3.0A; Output: 20V 6A)
- C13 to NEMA 5-15P Adapter, 4 ft.
- Owner's manual



Powering Business Worldwide

TRIPP LITE  
SERIES

USB-C + Laptop screen).

**Transmits Crystal-Clear 8K and 4K Video for Professional Editing and Digital Signage**Both the DisplayPort and Thunderbolt 3 video ports can achieve individual resolutions up to 8K (7680 x 4320) at 30 Hz, when used with a Thunderbolt 3-enabled source computer and Thunderbolt 3 cable. When used with an MFDP-enabled source computer, the DisplayPort connector's maximum resolution is 4K (3840 x 2160) at 60 Hz, and the Thunderbolt port is reduced to USB 2.0 data transfer functionality only. The Thunderbolt 3 port also allows daisy-chaining up to six devices, including RAID memory and other storage devices.

**USB Ports Connects Keyboards, Thumb Drives and Other USB Peripherals**Two USB-A hub ports and one USB-C port accept USB peripherals, such as flash drives, mice, keyboards, external hard drives and printers. All three support lightning-fast USB 3.2 Gen 2 data transfer rates up to 10 Gbps and are backward compatible with previous USB generations. The USB-C port supports USB charging up to 5V 1.5A. One USB-A port supports charging speeds up to 5V 1.5A. The other supports charging up to 5V 900mA.

**Accesses a Wired Gigabit Ethernet Network**The RJ45 port offers access to a Gigabit Ethernet network when no Wi-Fi is available or when a wired connection offers faster speeds. Connect using a UTP cable (sold separately), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

**Connects Stereo Audio Equipment for Recording and Playback**This Thunderbolt 3 docking station contains one 3.5 mm mini stereo jack, convenient for connecting speakers, headphones or a microphone to your workstation. You can listen to music or record the latest episode of your podcast.

**Allows External Memory Access**The SD 4.0 memory card slots support Micro SD and SD cards for transferring data to and from your connected computer or laptop. Both slots may be used at the same time.

**Included Thunderbolt 3 Cable Attaches in Either Direction**Unlike traditional USB cables that connect in only one direction, the reversible Thunderbolt 3 male connector plugs into its port in either direction for an instant connection every time.

**Ready to Use Right from the Package, So You Can Plug and Play Immediately**The plug-and-play Thunderbolt 3 dock is specifically designed for use with the MacBook Pro or Windows laptop equipped with a Thunderbolt 3 port. Drivers are automatically downloaded and installed during the initial dock connection with the host computer (Note: the host must have administrative access for the drivers to install automatically. If this is not possible the drivers can be downloaded manually via the product's web page at [tripplite.eaton.com](http://tripplite.eaton.com)). Simply plug the included power adapter into a standard AC outlet, and connect the included Thunderbolt 3 cable to your computer's Thunderbolt 3 or USB-C MFDP port.

## Specifications

| OVERVIEW       |                                                     |
|----------------|-----------------------------------------------------|
| UPC Code       | 037332250322                                        |
| Product Type   | Docking Station                                     |
| Technology     | Cat6; DisplayPort; Thunderbolt; USB 3.x             |
| Country/Region | North America                                       |
| Host Connector | THUNDERBOLT 3 (Type-C MALE)                         |
| VIDEO          |                                                     |
| Video Input    | THUNDERBOLT 3 (Type-C FEMALE)                       |
| Video Output   | DISPLAYPORT (FEMALE); THUNDERBOLT 3 (Type-C FEMALE) |

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of Monitors Supported   | 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Video Ports                    | THUNDERBOLT 3 (Type-C FEMALE); DISPLAYPORT (FEMALE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Video Ports Details            | DisplayPort 1.4; Thunderbolt 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Resolutions Supported          | <b>Thunderbolt 3 Host (with DisplayPort 1.4 Alt Mode):</b> Thunderbolt 3: 8K 30Hz (7680 x 4320); DisplayPort: 8K 30Hz (7680 x 4320) (Individually)Thunderbolt 3: 8K 30Hz (7680 x 4320) + DisplayPort: 4K 30Hz (3840 x 2160) (Dual Output) <b>USB-C MFDP Host (with DisplayPort 1.4 Alt Mode):</b> Thunderbolt 3: No Video (USB 2.0 Data only); DisplayPort: 4K 60Hz (3840 x 2160) (Single Output Only) <b>USB-C MFDP Host (with DisplayPort 1.2 Alt Mode):</b> Thunderbolt 3: No Video (USB 2.0 Data only); DisplayPort: 4K 30Hz (3840 x 2160) (Single Output Only) |
| Max Supported Video Resolution | 7680 x 4320 (8K) @ 30 Hz (Thunderbolt 3); 3840 x 2160 (4K x 2K) @ 60 Hz (MFDP)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Extended Mode                  | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Extended Mode Details          | <b>For Thunderbolt 3 Source:</b> 1x DP (8K 30Hz) + 1x ThunderBolt 3 (4K 30Hz) via USB-C to C or USB-C to DP or USB-C to HDMI cable or adapter <b>For USB-C MFDP Source:</b> 1x DP (4K 60Hz) <b>Note:</b> If USB-C host supports DP 1.2 Alt Mode instead of DP 1.4 Alt Mode, the maximum resolution is 4K/30 Hz                                                                                                                                                                                                                                                      |
| Mirror Mode                    | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Mirror Mode Details            | <b>For Thunderbolt 3 Source:</b> 1x DP (8K 30Hz) + 1x ThunderBolt 3 (4K 30Hz) via USB-C to C or USB-C to DP or USB-C to HDMI cable or adapter <b>For USB-C MFDP Source:</b> 1x DP (4K 60Hz) <b>Note:</b> If USB-C host supports DP 1.2 Alt Mode instead of DP 1.4 Alt Mode, the maximum resolution is 4K/30 Hz                                                                                                                                                                                                                                                      |
| Max Supported Color Depth      | 48-bit Deep Color                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| HDR Support                    | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| 3D Video Supported             | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Chroma Sub Sampling            | 4:4:4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| EDID Support                   | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Signal Transmission            | Unidirectional                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| DisplayPort Alt Mode           | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>AUDIO</b>                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Audio Ports                    | 3.5MM (FEMALE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Audio Ports Details            | 3.5mm Combo Stereo Audio / Microphone JackSupports 8/16/22.05/24/32/44.1/48/96/176.4/192/384 KHzSupports 16/24/32-Bit Sample RateSupports Auto-Detection and Auto-Switch between OMTP and CTIAIn order to extract sound the user must change the output sound manually in the sound setting of the source being used                                                                                                                                                                                                                                                |
| <b>DATA</b>                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Data Ports                     | (2) THUNDERBOLT 3 (Type-C FEMALE); (2) USB A (FEMALE); (1) USB C (FEMALE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Data Ports Details             | (2) USB-A - USB 3.2 Gen 2 (10 Gbps); (2) USB-C - ThunderBolt 3 (40 Gbps); (1) USB-C - USB 3.2 Gen 2 (10 Gbps)                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>NETWORK</b>                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Network Ports                  | RJ45 (FEMALE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>STORAGE</b>                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Card Slots                     | SD (FEMALE); MICRO SD (FEMALE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Card Slots Details             | Supports Secure Digital v.40 (SD 4.0) UHS-I (Ultra High Speed): SDR12 (12.5Mbyte/second)/SDR25 (25Mbyte/second)/SDR50 (50Mbyte/second)/SDR104 (104Mbyte/second)Supports UHS-II: Full Duplex Mode and Half Duplex Mode (Up to 312MB/s data rate)Both card readers can be used at the same time                                                                                                                                                                                                                                                                       |



Powering Business Worldwide

TRIPP LITE  
SERIES

| INPUT                                          |                                                                                               |
|------------------------------------------------|-----------------------------------------------------------------------------------------------|
| AC Power Adapter Plug(s)                       | NEMA 5-15P North America                                                                      |
| AC Power Adapter Input Specs (V / Hz / A)      | 100-240V / 50/60Hz / 3A                                                                       |
| AC Power Adapter Output Specs (V / A)          | 20V / 6A                                                                                      |
| AC Power Adapter Cord Length (ft.)             | 4                                                                                             |
| AC Power Adapter Cord Length (m)               | 1.2                                                                                           |
| Maximum Input Amps                             | 3.0                                                                                           |
| Voltage Compatibility (VAC)                    | 100; 110; 120; 125; 127; 200; 208; 220; 230; 240                                              |
| Bus Powered                                    | No                                                                                            |
| BATTERY                                        |                                                                                               |
| Battery Charging (5V/1.5A Port)                | Yes                                                                                           |
| POWER                                          |                                                                                               |
| Power Source Type                              | AC Adapter with detachable power cord                                                         |
| AC Adapter                                     | Input: 100–240V, 50/60 Hz, 3.0A; Output: 20V, 6A                                              |
| DC Barrel Plug                                 | OD: 4.5 x 0.6 x 10.5mm, Positive Pin, Negative Sleeve                                         |
| USB Power Delivery (PD) Charging Support       | Yes                                                                                           |
| USB Power Delivery (PD) Charging Specification | 60W                                                                                           |
| CONNECTIONS                                    |                                                                                               |
| Number of Ports                                | 10                                                                                            |
| Ports                                          | 1                                                                                             |
| Ports Detail                                   | Connect to a Gigabit Ethernet network with user-supplied Cat6 cabling                         |
| Dock Connectors                                | DISPLAYPORT, 2X THUNDERBOLT 3, USB-C CHARGING, RJ45 LAN, MICRO SD, SD, 3.5MM, 2X USB-A, USB-C |
| Side A - Connector 1                           | (2) THUNDERBOLT 3 (Type-C FEMALE)                                                             |
| Side A - Connector 2                           | DISPLAYPORT (FEMALE)                                                                          |
| Side A - Connector 3                           | RJ45 (FEMALE)                                                                                 |
| Side A - Connector 4                           | THUNDERBOLT 3 (Type-C MALE)                                                                   |
| Side A - Connector 5                           | USB A (FEMALE)                                                                                |
| Side B - Connector 2                           | MICRO SD (FEMALE); SD (FEMALE)                                                                |
| Side B - Connector 3                           | 3.5MM (FEMALE)                                                                                |
| Side B - Connector 4                           | (2) USB A (FEMALE); USB C (FEMALE)                                                            |
| Connector Plating                              | Nickel                                                                                        |



Powering Business Worldwide

TRIPP LITE  
SERIES

| USER INTERFACE, ALERTS & CONTROLS |                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LED Indicators                    | Green (Power), Orange (Transmitting Data)                                                                                                                                                                                                                                                                                                                                                          |
| CHARGING                          |                                                                                                                                                                                                                                                                                                                                                                                                    |
| Number of Charging Ports          | 5                                                                                                                                                                                                                                                                                                                                                                                                  |
| Total Charging Watts              | 60                                                                                                                                                                                                                                                                                                                                                                                                 |
| Charging Port Type                | (2) THUNDERBOLT 3 (Type-C FEMALE); (2) USB A (FEMALE); (1) USB C (FEMALE)                                                                                                                                                                                                                                                                                                                          |
| Charging Ports Details            | (2) Thunderbolt 3 ports: (1) Charges the host device with up to 60 Watts (5V/9V/15V/20V 3A); (1) Supports Thunderbolt 3 daisy chaining up to 6 levels with source capability of 15W (5V/3A)(2) USB 3.2 Gen 2 Type-A ports. (1) USB-A port supports USB charging up to 5V 1.5A. (1) USB-A port up to 4.5W (5V/0.9A).(1) USB 3.2 Gen 2 Type-C port which supports USB charging up to 7.5W (5V/1.5A). |
| Charging Ports / Amps             | (1) 0.9A; (2) 1.5A; (2) 3A                                                                                                                                                                                                                                                                                                                                                                         |
| Compatible Devices                | Chromebook; Laptop; Portable Speaker; Smartphone; Tablet                                                                                                                                                                                                                                                                                                                                           |
| PHYSICAL                          |                                                                                                                                                                                                                                                                                                                                                                                                    |
| Color                             | Black; Gray                                                                                                                                                                                                                                                                                                                                                                                        |
| Material of Construction          | PC, ABS, Aluminum                                                                                                                                                                                                                                                                                                                                                                                  |
| Cable Jacket Color                | Black                                                                                                                                                                                                                                                                                                                                                                                              |
| Cable Jacket Material             | PVC                                                                                                                                                                                                                                                                                                                                                                                                |
| Cable Outer Diameter (OD)         | 4.4mm                                                                                                                                                                                                                                                                                                                                                                                              |
| Cable Length (ft.)                | 1.64                                                                                                                                                                                                                                                                                                                                                                                               |
| Cable Length (m)                  | 0.50                                                                                                                                                                                                                                                                                                                                                                                               |
| Cable Length (in.)                | 19.69                                                                                                                                                                                                                                                                                                                                                                                              |
| Cable Length (cm)                 | 50                                                                                                                                                                                                                                                                                                                                                                                                 |
| Total Number of Ports             | 10                                                                                                                                                                                                                                                                                                                                                                                                 |
| Shipping Dimensions (hwd / in.)   | 2.44 x 9.72 x 6.85                                                                                                                                                                                                                                                                                                                                                                                 |
| Shipping Weight (kg)              | 0.38                                                                                                                                                                                                                                                                                                                                                                                               |
| Unit Dimensions (hwd / in.)       | 0.670 x 3.150 x 5.790                                                                                                                                                                                                                                                                                                                                                                              |
| Unit Dimensions (hwd / cm)        | 1.7 x 8.0 x 14.8                                                                                                                                                                                                                                                                                                                                                                                   |
| Unit Dimensions (hwd / mm)        | 17.5 x 80 x 148                                                                                                                                                                                                                                                                                                                                                                                    |
| Unit Packaging Type               | Box                                                                                                                                                                                                                                                                                                                                                                                                |
| Unit Weight (lbs.)                | 0.5952                                                                                                                                                                                                                                                                                                                                                                                             |
| Unit Weight (kg)                  | 0.27                                                                                                                                                                                                                                                                                                                                                                                               |
| ENVIRONMENTAL                     |                                                                                                                                                                                                                                                                                                                                                                                                    |
| Operating Temperature Range       | 32° to 113°F (0° to 45°C)                                                                                                                                                                                                                                                                                                                                                                          |
| Storage Temperature Range         | 32° to 158°F (0° to 70°C)                                                                                                                                                                                                                                                                                                                                                                          |
| Operating Humidity Range          | 10% to 85% RH, Non-Condensing                                                                                                                                                                                                                                                                                                                                                                      |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                       |                                                                               |
|---------------------------------------|-------------------------------------------------------------------------------|
| Storage Humidity Range                | 5 to 90% RH, Non-condensing                                                   |
| Power Provided to Connected Device(s) | USB-A 5V/1.5A (7.5W); USB-C 20V/3A (60W) to Host Computer                     |
| <b>COMMUNICATIONS</b>                 |                                                                               |
| Network Compatibility                 | 10 Mbps; 100 Mbps (Fast Ethernet); 1 Gbps (Gigabit)                           |
| <b>PORT EXPANSION</b>                 |                                                                               |
| Daisy-chainable or Cascadable         | Supports Thunderbolt 3 daisy chain up to 6 levels with up to 15 Watts (5V/3A) |
| <b>FEATURES &amp; SPECIFICATIONS</b>  |                                                                               |
| USB Hub Ports                         | Yes                                                                           |
| Number of USB Hub Ports               | 3                                                                             |
| USB Specification                     | USB 3.2 Gen 2 (Up to 10 Gbps)                                                 |
| Data Transfer Rate                    | 40 Gbps                                                                       |
| MST Support                           | Yes                                                                           |
| Ethernet Support                      | Yes                                                                           |
| UASP Support                          | No                                                                            |
| Auto MDIX Support                     | No                                                                            |
| Full Duplex Support                   | Yes                                                                           |
| Suspend Mode Support                  | No                                                                            |
| Remote Wakeup Support                 | No                                                                            |
| SD Card Specification                 | SD; Micro SD                                                                  |
| Thunderbolt Specification             | Thunderbolt 3 (up to 40Gbps short or active cables)                           |
| Displayport Specification             | 1.4                                                                           |
| HDCP Specification                    | 1.4; 2.2                                                                      |
| Driver Required                       | Yes                                                                           |
| Recommended Category Cable            | Cat5/Cat5e/Cat6 Cables                                                        |
| <b>STANDARDS &amp; COMPLIANCE</b>     |                                                                               |
| TAA Compliant Option                  | N                                                                             |
| External Power Supply Certifications  | CCC; CE; GS; PSE; TUV; UL; cUL                                                |
| Product Certifications                | NOM (Mexico)                                                                  |
| Product Compliance                    | FCC (USA); WEEE                                                               |
| <b>WARRANTY &amp; SUPPORT</b>         |                                                                               |
| Product Warranty Period (Worldwide)   | 3-year limited warranty                                                       |



*Powering Business Worldwide*

TRIPP LITE  
SERIES

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.