

PD-USB-PO30 Quick Start Guide

1. Connect an IEEE® 802.3af/at/bt-compliant PSE to the PD-USB-PO30's "PoE IN" RJ45 socket using a standard Cat 5/5e/6 Ethernet cable. (Note: The maximum allowed length of the Ethernet cable is 100 meters).



2. Check that the "Power" LED is yellow to verify that the PD-USB-PO30 is powered on.

3. Connect one side of the supplied USB Type-C® cable to the PD-USB-PO30's USB-C socket. (Note: Any USB-C connection polarity is allowed.)



4. Connect the other side of the USB Type-C cable to the USB-C powered device.
5. Verify that the USB-C powered device is getting power from the PD-USB-PO30.

LED Indicators

LED	Appearance	Status
Power	No Light	PD-USB-PO30 is powered off
	Yellow On	PD-USB-PO30 is powered on

Specifications

Power

- PoE IN
 - Input Voltage: 42-57 VDC
 - Input Current: 1.75A max
- USB Type-C
 - 5 V_{DC}/3A
 - 9 V_{DC}/2.61A
 - 15 V_{DC}/1.57A
 - 20 V_{DC}/1.18A

Environmental Information:

- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- Operating Humidity: 90% Max (non-condensing)
- Storage Temperature: -20°C to +70°C (-4°F to +158°F)
- Storage Humidity: 95% Max (non-condensing)
- Dimensions: 22.4 mm (H) x 66.8 mm (W) x 105.2 mm (L)
- Weight: 150g

Powering multiple PD-USB-DP30 from the same PoE multiport midspan may affect data/power performance to connected USB-C devices if they are sharing common peripheral equipment such as monitors, projectors, etc.

Technical Support

For technical support please visit the Microchip Technical Support Portal www.microchip.com/support