



Pushing Performance  
Since 1945

# PFT M12 shielded Harax B-cod.Female



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 21 03 341 2425                                                                        |
| Specification      | PFT M12 shielded Harax B-cod.Female                                                   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/21033412425">https://b2b.harting.com/21033412425</a> |

## Identification

|                |                                       |
|----------------|---------------------------------------|
| Category       | Connectors                            |
| Series         | Circular connectors M12               |
| Identification | M12-L                                 |
| Element        | Cable connector<br>Panel feed through |
| Specification  | for rear mounting                     |

## Version

|                    |                              |
|--------------------|------------------------------|
| Termination method | HARAX® connection technology |
| Gender             | Female                       |
| Shielding          | Shielded                     |
| Number of contacts | 2                            |
| Coding             | B-coding                     |
| Locking type       | Screw locking                |

## Technical characteristics

|                         |                   |
|-------------------------|-------------------|
| Conductor cross-section | 0.25 ... 0.34 mm² |
| Conductor cross-section | AWG 24 ... AWG 22 |
| Wire outer diameter     | ≤2.6 mm           |
| Rated current           | 4 A               |
| Rated voltage           | 32 V              |
| Rated impulse voltage   | 1.5 kV            |
| Pollution degree        | 3                 |



**Pushing Performance**  
Since 1945

## Technical characteristics

|                                        |                             |
|----------------------------------------|-----------------------------|
| Overvoltage category                   | III                         |
| Insulation resistance                  | $>10^8 \Omega$              |
| Contact resistance                     | $\leq 10 \text{ m}\Omega$   |
| Tightening torque                      | 2 Nm Lock nut               |
| Limiting temperature                   | -40 ... +85 °C              |
| Mating cycles                          | $\geq 100$                  |
| Degree of protection acc. to IEC 60529 | IP65 / IP67 mated condition |
| Cable diameter                         | 7 ... 8.8 mm                |
| Isolation group                        | I ( $600 \leq \text{CTI}$ ) |
| Thickness of the panel                 | 2.5 ... 4.5 mm              |

## Material properties

|                                      |                                                        |
|--------------------------------------|--------------------------------------------------------|
| Material (insert)                    | Polyamide (PA)                                         |
| Material (contacts)                  | Brass                                                  |
| Surface (contacts)                   | Au over Ni Mating side                                 |
| Material (hood/housing)              | Zinc die-cast                                          |
| RoHS                                 | compliant with exemption                               |
| RoHS exemptions                      | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                           | compliant with exemption                               |
| China RoHS                           | 50                                                     |
| REACH Annex XVII substances          | Not contained                                          |
| REACH ANNEX XIV substances           | Not contained                                          |
| REACH SVHC substances                | Yes                                                    |
| REACH SVHC substances                | Lead                                                   |
| ECHA SCIP number                     | 0d7d3693-d625-47ab-934a-d241bf72c86e                   |
| California Proposition 65 substances | Yes                                                    |
| California Proposition 65 substances | Lead                                                   |
|                                      | Nickel                                                 |
|                                      | Naphthalene                                            |
| Fire protection on railway vehicles  | EN 45545-2 (2020-08)                                   |
| Requirement set with Hazard Levels   | R26                                                    |

## Specifications and approvals

|                |                 |
|----------------|-----------------|
| Specifications | IEC 61076-2-101 |
|----------------|-----------------|



Pushing Performance  
Since 1945

Specifications and approvals

|          |                                   |
|----------|-----------------------------------|
| UL / CSA | UL 1977 ECBT2.E102079             |
|          | CSA-C22.2 No. 182.3 ECBT8.E102079 |

Commercial data

|                                |                                                  |
|--------------------------------|--------------------------------------------------|
| Packaging size                 | 1                                                |
| Net weight                     | 48.33 g                                          |
| Country of origin              | Germany                                          |
| European customs tariff number | 85366990                                         |
| GTIN                           | 5713140137950                                    |
| ETIM                           | EC002635                                         |
| eCl@ss                         | 27440116 Circular connector (for field assembly) |