

PFT male S- rear 1,5mm²



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 21 03 396 1402 |
| Specification | PFT male S- rear 1,5mm ² |
| HARTING eCatalogue | https://b2b.harting.com/21033961402 |

Identification

| | |
|----------------|--------------------------------------|
| Category | Connectors |
| Series | Circular connectors M12 |
| Identification | Power |
| Element | Panel feed through |
| Specification | With conductors for rear mounting |

Version

| | |
|-----------------------------------|---------------------------|
| Gender | Male |
| Shielding | Unshielded |
| Number of contacts | 4 |
| Number of power contacts | 3 |
| Number of special contacts | 1 |
| Specification of special contacts | PE contact |
| Coding | S-coding |
| Locking type | Screw locking PushPull |

Technical characteristics

| | |
|-------------------------|---------------------|
| Conductor cross-section | 1.5 mm ² |
| Conductor cross-section | AWG 16 |
| Rated current | 12 A |
| Rated voltage | 630 V |
| Rated impulse voltage | 6 kV |



Pushing Performance
Since 1945

Technical characteristics

| | |
|--|-----------------------------|
| Pollution degree | 3 |
| Overvoltage category | III |
| Insulation resistance | >10 ⁸ Ω |
| Contact resistance | ≤10 mΩ |
| Tightening torque | 0.8 Nm 2 Nm Lock nut |
| Limiting temperature | -40 ... +125 °C |
| Mating cycles | ≥100 |
| Degree of protection acc. to IEC 60529 | IP65 / IP67 mated condition |
| Isolation group | I (600 ≤ CTI) |
| Conductor length | 30 cm |

Material properties

| | |
|--------------------------------------|--|
| Material (insert) | Polyamide (PA) |
| Material (contacts) | Brass |
| Surface (contacts) | Au over Ni Mating side |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

| | |
|----------------|------------------------------------|
| Specifications | IEC 61076-2-111 IEC 61076-2-010 |
|----------------|------------------------------------|

Commercial data

| | |
|----------------|---|
| Packaging size | 1 |
|----------------|---|



Pushing Performance
Since 1945

Commercial data

| | |
|--------------------------------|---|
| Net weight | 41 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |
| GTIN | 5713140227750 |
| eCl@ss | 27440103 Sensor-actuator connector chassis (sensor technology actuator) |