



Image for illustrative purpose only

## Summary

[Request a quote](#)

[Catalog](#)

Number of contacts Low Voltage	4
Gender	Standard
Socket / Receptacle	Socket / Receptacle - Fixed Panel Rear Mounted
Locking system	Ratchet
Jacket cable outside diameter [mm]	4.85 - 9.70 mm
Size	1M
Suggested matching part	<a href="#">FGN.1M.304.XRCT2</a>
Series	M - Rugged Ratchet coupling

[https://www.lemo.com/int\\_en/solutions/optima/m-ratchet-coupling/pen-1m-304-xrmt2.html](https://www.lemo.com/int_en/solutions/optima/m-ratchet-coupling/pen-1m-304-xrmt2.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# Technical details

## Electrical Configuration

Contact Termination Low voltage	Crimp
Insert configuration value	1M.304_2 - 2 (0.7 mm) + 2 (1.3 mm) Low Voltage
Insulator	R: PEEK (mixed multipole)
Contact Type	Crimp
Number of contacts Low Voltage	4
Gender	Standard

## Form & Material

Shell style / Model id	PE - Fixed receptacle, nut fixing and mold stop
Socket / Receptacle	Fixed Panel Rear Mounted
Housing material	Aluminium (nickel plated [SAE AMS QQ N 290], anthracite color) shell and nut, other pieces bronze/brass
Locking system	Ratchet
Keying	N: 3 keys (beta=165, gamma=30, plug: male contacts, receptacle: female contacts)
Colour	Grey
Weight	8.25 g

## Environment

Technical domain	Motorsport, Security and Defence, Transportation, Aerospace and UAV
Environmental sealing (IP rating)	IP68
Endurance	3000 mating cycles
Temperature range	-20°C / +200°C
EMI Shielding EIA 364-66A	>= 80 dB (1 GHz), >=70 dB (3 GHz), >= 58 dB (6 GHz), >= 40 dB (10 GHz)
Gunfire vibration	25 Hz - 2000 Hz, 3 axis (Apache helicopter)
Humidity (max)	21 days at 95%
Lighting strike EIA 364-76	10K amps - 6 times
Shock Resistance	300 g [ 3 ms]
Thermal shock	5 cycles: -65°C to +150°C
Vibration-Random	37.8 g rms - 3 axes, 4 hr amb [50 Hz - 2000 Hz]
Vibration-Sine	30 g, 3 axes, 12 hr [10 Hz - 2000 Hz]
Salt Spray Corrosion	max. 48 hr



[https://www.lemo.com/int\\_en/solutions/optima/m-ratchet-coupling/pen-1m-304-xrmt2.html](https://www.lemo.com/int_en/solutions/optima/m-ratchet-coupling/pen-1m-304-xrmt2.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## Cable fixation

Cable termination protection	Heatshrink
Fixation type	T type cable adapter
Jacket cable outside diameter [mm]	4.85 - 9.70 mm

## Drawings



## Dimensions

	A	B	C	D	E	e	Ls	Lr	M	P	R	S1	S2
mm.	18	10.5	17.8	9.7	5	M14x1.00	25.6	25.6	9.7	5.3	13.8	12.5	16
in.	0.71	0.41	0.7	0.38	0.2		1.01	1.01	0.38	0.21	0.54	0.49	0.63

## Recommended By Lemo

### Accessories

Replacement contact	<a href="#">EGN.0M.655.ZZM</a>
Compatible cap	<a href="#">BGK.1M.200.XAZ</a>

### Tools

Positionner	<a href="#">DCE.91.130.5MVM</a>
Positionner 2	<a href="#">DCE.91.070.3MVM</a>
Extraction tool	<a href="#">DCF.93.131.4LT</a>
Extraction tool 2	<a href="#">DCF.93.070.4LT</a>
Spanner wrench	<a href="#">DCM.65.160.AZ</a>

[https://www.lemo.com/int\\_en/solutions/optima/m-ratchet-coupling/pen-1m-304-xrmt2.html](https://www.lemo.com/int_en/solutions/optima/m-ratchet-coupling/pen-1m-304-xrmt2.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.