



Image for illustrative purpose only

## Summary

[Request a quote](#)

[Catalog](#)

|                                    |   |
|------------------------------------|---|
| Nb of contacts Coax                | 4   |
| Number of contacts Low Voltage     | 9   |
| Gender                             | Standard  |
| Socket / Receptacle                | Socket / Receptacle - Fixed Panel Front Mounted |
| Locking system                     | Push-pull                                       |
| Jacket cable outside diameter [mm] | 4.00 - 28.60 mm                                 |
| Size                               | 4K  |
| Suggested matching part            | <a href="#">FGG.4K.879.CLAC121</a>              |
| Series                             | K - Outdoor keyed                               |

[https://www.lemo.com/int\\_en/solutions/originals/k-outdoor-keyed/egg-4k-879-cll1.html](https://www.lemo.com/int_en/solutions/originals/k-outdoor-keyed/egg-4k-879-cll1.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# Technical details

## Electrical Configuration

|                                 |                                    |
|---------------------------------|------------------------------------|
| Contact Termination Low voltage | Solder                             |
| Nb of contacts Coax             | 4                                  |
| Contact Termination Coax        | Crimp                              |
| R (max)                         | 5.8 mOhm                           |
| Insert configuration value      | 4K.879 - 4 Coax (50 Ohm), 9 Low V. |
| Insulator                       | L: PEEK (UL 94 / V-0/1.5)          |
| Rated current                   | 7 A                                |
| Test voltage (kV DC)            | 1.3                                |
| Contact Type                    | Coaxial 50 Ohm (Crimp) Type C      |
| Cable type                      | RG 174 A/U, RG 188 A/U, RG 316 /U  |
| Contact Dia.                    | 0.7 mm (0.03in)                    |
| Number of contacts Low Voltage  | 9                                  |
| Gender                          | Standard                           |

## Form & Material

|                        |  |
|------------------------|--|
| Shell style / Model id | EG - Fixed receptacle, nut fixing  |
| Socket / Receptacle    | Fixed Panel Front Mounted  |
| Housing material       | Brass (chrome plated [SAE AMS 2460]) shell, collet nut and latch sleeve, nickel plated [SAE AMS QQ N 290] brass mid pieces |
| Locking system         | Push-pull  |
| Keying                 | G: 1 key (alpha=0, plug: male contacts, receptacle: female contacts)   |
| Colour                 | Grey   |
| Weight                 | 111.43 g   |

[https://www.lemo.com/int\\_en/solutions/originals/k-outdoor-keyed/egg-4k-879-cll1.html](https://www.lemo.com/int_en/solutions/originals/k-outdoor-keyed/egg-4k-879-cll1.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.



## Environment

|                                   |   |
|-----------------------------------|---|
| Technical domain                  | Audio Video, Energy and Industrial, Medical, Test and Measurement |
| Environmental sealing (IP rating) | IP68  |
| Endurance                         | 5000 mating cycles  |
| Temperature range                 | -55°C / +200°C  |
| Climatical Category               | 50/175/21   |
| Humidity (max)                    | <=95% [at 60 deg C /140 F]  |
| Shielding (min)                   | 95 dB (10 MHz)  |
| Shielding (min)                   | 80 dB (1 GHz)   |
| Shock Resistance                  | 100 g [ 6 ms]   |
| Vibration                         | 15 g [10 Hz - 2000 Hz]  |
| Salt Spray Corrosion              | >1000 hr  |

## Cable fixation

|                                    |                 |
|------------------------------------|-----------------|
| Jacket cable outside diameter [mm] | 4.00 - 28.60 mm |
|------------------------------------|-----------------|

## Drawings



## Dimensions

|     | <b>A</b> | <b>B</b> | <b>e</b> | <b>E</b> | <b>L</b> | <b>M</b> | <b>N</b> | <b>S3</b> | <b>S1</b> |
|-----|----------|----------|----------|----------|----------|----------|----------|-----------|-----------|
| mm. | 37       | 41.5     | M30x1.0  | 9        | 40.2     | 6.5      | 38.6     | 36        | 28.5      |
| in. | 1.46     | 1.63     |          | 0.35     | 1.58     | 0.26     | 1.52     | 1.42      | 1.12      |

[https://www.lemo.com/int\\_en/solutions/originals/k-outdoor-keyed/egg-4k-879-cll1.html](https://www.lemo.com/int_en/solutions/originals/k-outdoor-keyed/egg-4k-879-cll1.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# Recommended By Lemo

## Accessories

---

|                |                                |
|----------------|--------------------------------|
| Compatible cap | <a href="#">BRE.4K.200.NAS</a> |
|----------------|--------------------------------|

## Tools

---

|          |                               |
|----------|-------------------------------|
| Die Tool | <a href="#">DPE.99.103.8K</a> |
|----------|-------------------------------|

|                 |                                |
|-----------------|--------------------------------|
| Extraction tool | <a href="#">DCC.91.384.5LA</a> |
|-----------------|--------------------------------|

[https://www.lemo.com/int\\_en/solutions/originals/k-outdoor-keyed/egg-4k-879-cll1.html](https://www.lemo.com/int_en/solutions/originals/k-outdoor-keyed/egg-4k-879-cll1.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.