

## SmartRack 12U Mid-Depth Small Rack Enclosure

MODEL NUMBER: SR12UB



Ideal for data centers and IT environments that need a secure, mid-depth and heavy-duty rack enclosure cabinet capable of supporting up to 1,000 lbs. of equipment in a full 12U of rack space.

### Description

This SmartRack® 12U Mid-Depth Rack Enclosure Cabinet is designed to simplify rack equipment installations and rack equipment maintenance. Compatible with all standard 19-inch rack equipment, it features front and rear pairs of vertical rails with square mounting holes. The rails are adjustable in quarter-inch increments to accommodate equipment depths from three to 32.5 inches, ideal for standard server installation. The rails are capable of supporting up to 1,000 pounds (453.6 kilograms) of equipment. The top and bottom panels are provided with ports for cable routing, and are furnished with vents designed to help remove warm air from the enclosure and draw in cool air by convection. The panels also support installation of standard user-supplied case fans (SRFANWM, sold separately). With a locking reversible front/rear doors and locking removable side panels, the SR12UB provides for the safe, secure installation of all equipment. To simplify deployment, the SR12UB comes with an accessory caster kit so it can easily be maneuvered into the desired location, and then secured in place by adjusting the unit's levelers. It ships fully assembled for quick installation.

### Features

#### Simple Installation:

Compatible with all standard 19-inch rack equipment and is designed to simplify equipment installation. It features front and rear pairs of vertical rails with square mounting holes. The rails are adjustable in quarter-inch increments to accommodate equipment depths from 3 to 32.5 inches. The rails feature square mounting holes and are capable of supporting up to 1000 pounds (453.6 kg) of equipment with included installation hardware. The top and bottom panels are also provided with ports for cable routing. Each rack space within the enclosure is numbered for easy reference.

#### Secure Equipment Access:

Designed to provide a safe, secure installation solution for up to 1000 pounds (453.6 kg) of mission-critical rack-mount equipment. It features a locking, reversible front/rear doors and locking, removable side panels. This prevents unauthorized access to installed equipment while making it easy for authorized personnel to perform inspections, maintenance and equipment replacement.

#### Convection Cooling:

The top and bottom panels are furnished with vents designed to help remove warm air from the enclosure and draw in cool air by convection. The panels also support installation of standard user-supplied case fans (SRFANWM).

#### Vented Top and Bottom Panels with Cable Cutouts:

The top and bottom panels are furnished with vents designed to help remove warm air from the enclosure and draw in cool air by convection. They also support installation of standard user-supplied case fans.

### Highlights

- Premium SmartRack mid-depth enclosure cabinet
- 12U of rack space; 1000 lbs (453.6 kgs) load capacity
- Depth of 33" allow for standard server installation
- Locking, reversible front/rear doors and locking, removable side panels
- Casters and leveling feet
- Meets all enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) compliance

### Package Includes

- SmartRack 12U Mid-Depth Rack Enclosure Cabinet
- (36) M6 screws
- (36) M6 cage nuts
- (36) M6 washers
- SRACASTER kit (includes 4 casters)
- (2) keys
- Owner's Manual



Powering Business Worldwide

TRIPP LITE  
SERIES

#### Casters for Mobility:

Comes with an accessory caster kit consisting of 4 casters and all required installation hardware. With the casters installed, the SR12UB can easily be maneuvered into the desired location, and then secured in place by adjusting the unit's levelers. Note: the casters are intended for minor position adjustments within the final installation area only and are not designed for moving the enclosure over long distances.

## Specifications

| OVERVIEW                               |                                          |
|----------------------------------------|------------------------------------------|
| UPC Code                               | 037332157911                             |
| Device Compatibility                   | Patch Panel; Network Switch; UPS; Server |
| Rack Type                              | Small Enclosure                          |
| PHYSICAL                               |                                          |
| Color                                  | Black                                    |
| Rack Height                            | 12U                                      |
| Rack Depth                             | Mid                                      |
| Factory Preset Rack Depth (in.)        | 28.31                                    |
| Factory Preset Rack Depth (cm)         | 71.9                                     |
| Factory Preset Rack Depth (mm)         | 719                                      |
| Maximum Device Depth (cm)              | 82.55                                    |
| Maximum Device Depth (in.)             | 32.5                                     |
| Maximum Device Depth (mm)              | 826                                      |
| Minimum Device Depth (cm)              | 7.62                                     |
| Minimum Device Depth (in.)             | 3                                        |
| Minimum Device Depth (mm)              | 76                                       |
| Cable Access Hole Measurement (inches) | 9.812 x 2.35 (l x w)                     |
| Shipping Dimensions (hwd / in.)        | 31.00 x 37.00 x 27.00                    |
| Shipping Dimensions (hwd / cm)         | 78.74 x 93.98 x 68.58                    |
| Shipping Weight (lbs.)                 | 112.00                                   |
| Shipping Weight (kg)                   | 50.80                                    |
| Unit Dimensions (hwd / in.)            | 25.100 x 23.600 x 33.500                 |
| Unit Dimensions (hwd / cm)             | 63.75 x 60 x 85.09                       |
| Unit Weight (lbs.)                     | 105                                      |
| Unit Weight (kg)                       | 47.63                                    |
| Weight Capacity - Rolling (kg)         | 454                                      |
| Weight Capacity - Rolling (lbs.)       | 1000                                     |
| Weight Capacity - Stationary (kg)      | 454                                      |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                            |
|--------------------------------------|----------------------------|
| Weight Capacity - Stationary (lbs.)  | 1000                       |
| Number of Vertical Mounting Rails    | 4                          |
| Assembly Required                    | Yes                        |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                            |
| Grounding Details                    | Front and Back door frames |
| Pre-Installed Casters                | No                         |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                            |
| Product Certifications               | UL 60950-1                 |
| Product Compliance                   | RoHS; EIA/ECA-310-E; UKCA  |
| <b>WARRANTY &amp; SUPPORT</b>        |                            |
| Product Warranty Period (Worldwide)  | 5-year limited warranty    |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.