


## USB 2.0 A Female to USB Motherboard 4-PIN IDC Header Cable, 6-in. (15.24 cm)

MODEL NUMBER: U024-06N-IDC



### Highlights

- 6-inch USB "A" Female to 4-pin IDC motherboard connector
- Plug and Play

### Package Includes

- 6" USB 2.0 A Female to USB Motherboard 4-PIN IDC Header Cable

Connect an internal USB device to a USB 4-pin motherboard header connector

### Features

- 6-inch USB 2.0 Female to USB Motherboard 4-pin IDC Header cable
- USB 2.0 rated ( 480mbps )
- Allows motherboard connection for internal USB devices

## Specifications

| OVERVIEW                        |                      |
|---------------------------------|----------------------|
| UPC Code                        | 037332185457         |
| Technology                      | USB 2.0 (High Speed) |
| Cable Type                      | Passive              |
| CONNECTIONS                     |                      |
| Side A - Connector 1            | 4 PIN (INTERNAL)     |
| Side B - Connector 1            | USB A (FEMALE)       |
| Connector Style                 | Straight             |
| PHYSICAL                        |                      |
| Cable Jacket Color              | Black                |
| Cable Length (ft.)              | 0.5                  |
| Cable Length (m)                | 0.15                 |
| Shipping Dimensions (hwd / in.) | 9.00 x 7.00 x 0.50   |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                     |                              |
|-------------------------------------|------------------------------|
| Shipping Dimensions (hwd / cm)      | 22.86 x 17.78 x 1.27         |
| Shipping Weight (lbs.)              | 0.03                         |
| Shipping Weight (kg)                | 0.01                         |
| <b>ENVIRONMENTAL</b>                |                              |
| Operating Temperature Range         | 14° to 122°F (-10° to 50°C)  |
| Storage Temperature Range           | 5° to 140°F (-15° to 60°C)   |
| Operating Humidity Range            | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range              | 0% to 88% RH, Non-Condensing |
| <b>STANDARDS &amp; COMPLIANCE</b>   |                              |
| Product Compliance                  | RoHS                         |
| <b>WARRANTY &amp; SUPPORT</b>       |                              |
| Product Warranty Period (Worldwide) | Lifetime limited warranty    |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.