

## Han-Compact hood TE/SE M20



Image is for illustration purposes only. Please refer to product description.

Part number	19 12 008 0425
Specification	Han-Compact hood TE/SE M20
HARTING eCatalogue	<a href="https://harting.com/19120080425">https://harting.com/19120080425</a>

### Identification

Category	Hoods / Housings
Series of hoods/housings	Han-Compact®
Type of hood/housing	Hood

### Version

Size	Han-Compact®
Version	Top/side entry
Number of cable entries	2
Cable entry	2x M20
Locking type	Single locking lever
Field of application	Hoods/housings for industrial applications

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

### Material properties

Material (hood/housing)	Polycarbonate (PC)
Colour (hood/housing)	RAL 9005 (jet black)
Material flammability class acc. to UL 94	V-0



Pushing Performance  
Since 1945

## Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

## Specifications and approvals

Approvals	CE DNV GL
-----------	--------------

## Commercial data

Packaging size	5
Net weight	33.3 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140124103
ETIM	EC000437
eCl@ss	27440202 Shell for industrial connectors