

## Han Yellock 60HSM 1xM40 with bulkhead h.



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 11 12 600 1213  |
| Specification      | Han Yellock 60HSM 1xM40 with bulkhead h.                                      |
| HARTING eCatalogue | <a href="https://harting.com/11126001213">https://harting.com/11126001213</a> |

### Identification

|                             |                                 |
|-----------------------------|---------------------------------|
| Category                    | Hoods / Housings                |
| Series of hoods/housings    | Han-Yellock®                    |
| Type of hood/housing        | Surface mounted housing         |
| Description of hood/housing | incl. bulkhead mounted housings |

### Version

|                         |  |
|-------------------------|--|
| Size                    | Han-Yellock® 60                            |
| Version                 | Side entry                                 |
| Number of cable entries | 1  |
| Cable entry             | 1x M40                                     |
| Locking type            | Screw locking                              |
| Field of application    | Hoods/housings for industrial applications |

### Technical characteristics

|  |  |
|--|--|
| Limiting temperature                   | -40 ... +125 °C                                |
| Note on the limiting temperature       | For use as a connector according to IEC 61984. |
| Un-/locking temperature                | -10 ... +85 °C                                 |
| Degree of protection acc. to IEC 60529 | IP65<br>IP67                                   |

### Material properties

|                         |                    |
|-------------------------|--------------------|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing)  | Powder-coated      |



**Pushing Performance**  
Since 1945

## Material properties

|   |                       |
|---|-----------------------|
| Colour (hood/housing)                     | RAL 7021 (black grey) |
| Material (seal)                           | NBR                   |
| Material flammability class acc. to UL 94 | V-0                   |
| RoHS                                      | compliant             |
| ELV status                                | compliant             |
| China RoHS                                | e                     |
| REACH Annex XVII substances               | Not contained         |
| REACH ANNEX XIV substances                | Not contained         |
| REACH SVHC substances                     | Not contained         |
| California Proposition 65 substances      | Yes                   |
| California Proposition 65 substances      | Lead<br>Nickel        |

## Specifications and approvals

|                |                          |
|----------------|--------------------------|
| Specifications | IEC 60664-1<br>IEC 61984 |
| Approvals      | CE<br>DNV GL             |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Net weight                     | 610 g                                    |
| Country of origin              | China                                    |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140110298                            |
| ETIM                           | EC000437                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |