

Han DD Quick-Lock module, female Au




Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 14 012 2734 |
| Specification | Han DD Quick-Lock module, female Au |
| HARTING eCatalogue | https://b2b.harting.com/09140122734 |

Identification

| | |
|--------------------|----------------|
| Category | Modules |
| Series | Han-Modular® |
| Type of module | Han DD® module |
| Size of the module | Single module |

Version

| | |
|--------------------|--|
| Termination method | Han-Quick Lock® termination |
| Gender | Female |
| Number of contacts | 12 |
| Details | Black slide |
| Details | for stranded wire according to IEC 60228 Class 5 |

Technical characteristics

| | |
|--------------------------|------------------------------|
| Conductor cross-section | 0.25 ... 1.5 mm ² |
| Wire outer diameter | ≤3.6 mm |
| Rated current | 10 A |
| Rated voltage | 250 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 3 |
| Rated voltage acc. to UL | 600 V |
| Insulation resistance | >10 ¹⁰ Ω |
| Contact resistance | ≤3 mΩ |



Pushing Performance
Since 1945

Technical characteristics

| | |
|----------------------|-----------------|
| Stripping length | 10 mm |
| Limiting temperature | -40 ... +125 °C |
| Mating cycles | ≥500 |

Material properties

| | |
|---|--|
| Material (insert) | Polycarbonate (PC) |
| Colour (insert) | RAL 7032 (pebble grey) |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Gold plated |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | 5dbb3851-b94e-4e88-97a1-571845975242 |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |

Specifications and approvals

| | |
|----------------|--|
| Specifications | IEC 60664-1 IEC 61984 |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
| Approvals | DNV GL |

Commercial data

| | |
|----------------|---|
| Packaging size | 2 |
|----------------|---|



Pushing Performance
Since 1945

Commercial data

| | |
|--------------------------------|---|
| Net weight | 10 g |
| Country of origin | Romania |
| European customs tariff number | 85389099 |
| GTIN | 5713140020948 |
| ETIM | EC000438 |
| eCl@ss | 27440217 Module for industrial connectors (power/signals) |