



SKiM® 93

Trench IGBT Modules

SKiM909GD066HD

Features


- IGBT 3 Trench Gate Technology
- Solderless sinter technology
- $V_{CE(sat)}$ with positive temperature coefficient
- Low inductance case
- Isolated by Al_2O_3 DCB (Direct Copper Bonded) ceramic substrate
- Pressure contact technology for thermal contacts
- Spring contact system to attach driver PCB to the control terminals
- High short circuit capability, self limiting to $6 \times I_C$
- Integrated temperature sensor

Typical Applications*

- Automotive inverter
- High reliability AC inverter wind
- High reliability AC inverter drives

Remarks

- Case temperature limited to $T_s = 125^\circ C$ max; $T_c = T_s$ (for baseplateless modules)
- Recommended $T_{op} = -40 \dots +150^\circ C$



GD

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
IGBT				
V _{CES}			600	V
I _C	T _j = 175 °C	T _s = 25 °C	899	A
		T _s = 70 °C	715	A
I _{Cnom}			900	A
I _{CRM}	I _{CRM} = 2xI _{Cnom}		1800	A
V _{GES}			-20 ... 20	V
t _{psc}	V _{CC} = 360 V V _{GE} ≤ 15 V V _{CES} ≤ 600 V	T _j = 150 °C	6	μs
T _j			-40 ... 175	°C
Inverse diode				
I _F	T _j = 175 °C	T _s = 25 °C	712	A
		T _s = 70 °C	550	A
I _{Fnom}			900	A
I _{FRM}	I _{FRM} = 2xI _{Fnom}		1800	A
I _{FSM}	t _p = 10 ms, sin 180°, T _j = 25 °C		4320	A
T _j			-40 ... 175	°C
Module				
I _{t(RMS)}	T _{terminal} = 80 °C		700	A
T _{stg}			-40 ... 125	°C
V _{isol}	AC sinus 50 Hz, t = 1 min		2500	V

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT						
V _{CE(sat)}	I _C = 900 A V _{GE} = 15 V chipelevel	T _j = 25 °C		1.45	1.85	V
		T _j = 150 °C		1.70	2.10	V
V _{CE0}	V _{GE} = 15 V	T _j = 25 °C		0.9	1	V
		T _j = 150 °C		0.85	0.9	V
r _{CE}		T _j = 25 °C		0.6	0.9	mΩ
		T _j = 150 °C		0.9	1.3	mΩ
V _{GE(th)}	V _{GE} =V _{CE} , I _C = 14.4 mA		5	5.8	6.5	V
I _{CES}	V _{GE} = 0 V	T _j = 25 °C		0.1	0.3	mA
	V _{CE} = 600 V	T _j = 150 °C				mA
C _{ies}	V _{CE} = 25 V V _{GE} = 0 V	f = 1 MHz		55.44		nF
C _{oes}		f = 1 MHz		3.46		nF
C _{res}		f = 1 MHz		1.64		nF
Q _G	V _{GE} = - 8 V...+ 15 V			7200		nC
R _{Gint}	T _j = 25 °C			0.3		Ω
t _{d(on)}	V _{CC} = 300 V I _C = 900 A	T _j = 150 °C		570		ns
t _r		T _j = 150 °C		160		ns
E _{on}	R _{G on} = 3 Ω	T _j = 150 °C		36		mJ
t _{d(off)}	R _{G off} = 3 Ω	T _j = 150 °C		1290		ns
t _f	di/dt _{on} = 5100 A/μs	T _j = 150 °C		90		ns
E _{off}	di/dt _{off} = 9000 A/μs	T _j = 150 °C		88		mJ
R _{th(j-s)}	per IGBT				0.078	K/W



SKiM® 93

Trench IGBT Modules

SKiM909GD066HD

Features

- IGBT 3 Trench Gate Technology
- Solderless sinter technology
- $V_{CE(sat)}$ with positive temperature coefficient
- Low inductance case
- Isolated by Al_2O_3 DCB (Direct Copper Bonded) ceramic substrate
- Pressure contact technology for thermal contacts
- Spring contact system to attach driver PCB to the control terminals
- High short circuit capability, self limiting to $6 \times I_C$
- Integrated temperature sensor


Typical Applications*

- Automotive inverter
- High reliability AC inverter wind
- High reliability AC inverter drives

Remarks

- Case temperature limited to $T_s = 125^\circ\text{C}$ max; $T_c = T_s$ (for baseplateless modules)
- Recommended $T_{op} = -40 \dots +150^\circ\text{C}$

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Inverse diode						
V _F = V _{EC}	I _F = 900 A V _{GE} = 0 V chiplevel	T _j = 25 °C		1.5	1.8	V
		T _j = 150 °C		1.6	1.8	V
V _{F0}		T _j = 25 °C		1	1.1	V
		T _j = 150 °C		0.85	0.95	V
r _F		T _j = 25 °C		0.6	0.7	mΩ
		T _j = 150 °C		0.8	0.9	mΩ
I _{RRM}		I _F = 900 A	T _j = 150 °C		500	A
Q _{rr}	di/dt _{off} = 4800 A/μs	T _j = 150 °C		118		μC
E _{rr}	V _{GE} = -15 V	T _j = 150 °C		29		mJ
	V _{CC} = 300 V					
R _{th(j-s)}	per diode				0.135	K/W
Module						
L _{CE}				10	15	nH
R _{CC'+EE'}	terminal-chip	T _s = 25 °C		0.3		mΩ
		T _s = 125 °C		0.5		mΩ
w				1042		g
Temperature Sensor						
R ₁₀₀	T _{Sensor} = 100 °C (R ₂₅ = 5 kΩ)			339		Ω
B _{100/125}	R _(T) = R ₁₀₀ exp[B _{100/125} (1/T-1/373)]; T[K];			4096		K



GD




Fig. 1: Typ. output characteristic, inclusive $R_{CC'} + EE'$




Fig. 2: Rated current vs. temperature $I_C = f(T_C)$




Fig. 3: Typ. turn-on /-off energy = $f(I_C)$




Fig. 4: Typ. turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. transfer characteristic












Fig. 6: Typ. gate charge characteristic





SKIM 93



GD

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX

* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our staff.