

Kellems Wire Management, Cord  
Connectors, Straight Male, .63-.75",  
3/4", Aluminum

By Hubbell Wiring Device-Kellems  
Catalog # [SHC1037](#)

Kellems Wire Management, Cord Connectors, Straight Male,  
.63-.75", 3/4", Aluminum

Application

- Straight Male- Form 3

Performance

- Environmental - Hazardous Locations - Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC
- Environmental - Operating Temperatures - -30°F to +225°F (-34°C to +107°C)

General

|                              |                                                                                                                                                                                            |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number               | SHC1037                                                                                                                                                                                    |
| Color Code                   | Yellow                                                                                                                                                                                     |
| EU RoHS Indicator            | Yes                                                                                                                                                                                        |
| Environmental Conditions     | Suitable For Use In Wet Locations When Used With A Listed Nylon Washer Between Box And Fitting.                                                                                            |
| Item Type                    | Cord Connectors                                                                                                                                                                            |
| Material                     | Aluminum                                                                                                                                                                                   |
| Material - Mounting Hardware | Locknut or Tapped Opening                                                                                                                                                                  |
| OEM Brand Name               | Hubbell Wiring Device-Kellems                                                                                                                                                              |
| Series                       | Standard Duty                                                                                                                                                                              |
| Specifications               | <ul style="list-style-type: none"><li>Cord Diameter Range Inches (mm) - .63"-.75" (15.9-19.0)</li><li>Form Size - F3</li><li>Material - Aluminum</li><li>NPT Hub Size - 3/4 Inch</li></ul> |
| Temperature Rating           | Minimum -30 Deg F to 225 Deg F (-34 Deg C to 107 Deg C)                                                                                                                                    |
| Type                         | Straight Male                                                                                                                                                                              |
| UPC                          | 783585200378                                                                                                                                                                               |

Dimensions



|              |          |
|--------------|----------|
| Display Size | 3/4" NPT |
| Hub Size     | 3/4"     |

Conductor Related

|                      |                               |
|----------------------|-------------------------------|
| Conductor Range      | 0.63- 0.75 in (15.9- 19.0 mm) |
| Number of Conductors | Single                        |

Certifications And Compliance

|                             |                            |
|-----------------------------|----------------------------|
| Industry Standard(s)        | UL Listed                  |
| Nema Rating                 | NEMA Type 4, 4X, 12 and 13 |
| Standards - RoHS Compliance | CM                         |
| Status                      |                            |

Logistics

|                 |      |
|-----------------|------|
| Carton Quantity | 30   |
| Pallet Quantity | 9600 |

Product Assets

- [Catalog Page - WDK W-69](#)
- [Catalog Page - WDK W-70](#)
- [Catalogs - WDK Catalog Full 2024](#)
- [Engineering Drawing - SHC1037 AutoCAD Drawing](#)
- [Installation Manuals - WIRING\\_PD1856\\_INSTALLINST](#)
- [Literature - Wire Management Solutions Brochure](#)
- [Literature - FOOD & BEVERAGE SOLUTIONS](#)
- [Literature - PULP & PAPER SOLUTIONS](#)
- [Literature - Pulp & Paper Solutions](#)
- [Literature - FOOD & BEVERAGE SOLUTIONS](#)
- [Literature - Entertainment Product Solution Guide](#)
- [Sales Drawings - WDK\\_SHC10\\_DRAWING\\_PDF](#)
- [Specifications - Wiring SHC1037 Specification Sheet](#)
- [Warranty - Industrial & Commercial Products](#)
- [Video - Kellems Wire Management Solutions](#)