

DTP06-4S-E004 ✓ ACTIVE

DEUTSCH | DEUTSCH DT, DEUTSCH DTP

TE Internal #: DTP06-4S-E004

4 Position Housing, Housing for Female Terminals, Wire-to-Wire, 6.7 mm [.264 in] Centerline, Sealable, Black, Wire & Cable, Power, Hybrid

[View on TE.com >](#)



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DTP Housings



Number of Positions: 4

Connector & Housing Type: **Housing for Female Terminals**

Mating Pin Diameter: 2.39 mm [.094 in]

Connector System: **Wire-to-Wire**

Centerline (Pitch): 6.7 mm [.264 in]

[All DEUTSCH DTP Housings \(34\)](#)

Features

Industry Standards

IP Rating	IP6K9K, IP68
Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	UL 94V-0

Dimensions

Row-to-Row Spacing	10.2 mm[.4 in]
Compatible Insulation Diameter Range	3.4 – 4.9 mm[.134 – .195 in]
Product Width	22 mm[.866 in]
Product Length	24.4 mm[.96 in]
Connector Height	34.6 mm[1.36 in]

Packaging Features

Packaging Quantity	1
Packaging Method	Package



Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	No
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Other

Serviceable	Yes
Connector Position Assurance Capable	No
EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant

Electrical Characteristics

Operating Voltage	200 VDC
Nominal Voltage Architecture	200 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Black

Housing Features

Housing Material	PA GF
Centerline (Pitch)	6.7 mm[.264 in]

Contact Features

Contact Size	Size 12
Contact Type	Socket
Mating Pin Diameter	2.39 mm[.094 in]
Contact Current Rating (Max)	25 A

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Primary Locking Feature	Integrated in Housing



Connector & Contact Terminates To	Wire & Cable
-----------------------------------	--------------

Configuration Features

Blank Cavity Position	0
Number of Positions	4
Number of Rows	2

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Octamethylcyclotetrasiloxane (D4) (.5% in Component Part) Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part) Decamethylcyclopentasiloxane (D5) (.5% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous





materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts










Also in the Series | DEUTSCH DT



Also in the Series | DEUTSCH DTP






Insertion & Extraction Tools(3)




Other Automotive Connector Accessories(4)



PCB Headers & Receptacles(5)



Rectangular Backshells & Clamps(3)



Wire-to-Board Headers & Receptacles (5)

Customers Also Bought



TE Part #DT04-12PA-BE02
REC, 12P, GRY, N, ENH KEY, CAP, A



TE Part #DT06-08SC-EP06
PLG, 8P, GRN, N, SEAL RET, CAP, C




TE Part #CAT-H396-CH8172
DEUTSCH HDP20 Housings




TE Part #8-36917-3
TERMINAL,SOLIS R 1/0 3/8



TE Part #DTP04-2P-E004
REC, 2P, BLK, N



TE Part #CM9613-000
SBP050100WE10



TE Part #172059-1
MALE HSG DRAWER



TE Part #WP-4S
WEDGE LOCK, 4P, PLG, ORG, DTP



TE Part #M902-2193
BKSHL, 9SZ, CBL SZ .430-.570, HD10

Documents



Product Drawings

[PLG, 4P, BLK, N](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_DTP06-4S-E004_99_c-dtp06-4s-e004-99.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_DTP06-4S-E004_99_c-dtp06-4s-e004-99.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_DTP06-4S-E004_99_c-dtp06-4s-e004-99.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[ICT Terminals and Connectors Catalogue](#)

English

[CONNECTOR SELECTOR](#)

English

Product Specifications

[Application Specification](#)

English

Agency Approvals

[UL Report](#)

English