


## Duplex Singlemode 9/125 Fiber Patch Cable (LC/SC), 1M (3 ft.)

MODEL NUMBER: N366-01M



### Highlights

- Premium PVC 9/125 micron singlemode patch cables
- Attenuation loss meets or exceeds the latest industry standards
- Twice the bandwidth throughput of multimode cable

### System Requirements

- Any fiber optic hardware or NIC card requiring singlemode duplex cable with LC/SC connectors

### Package Includes

- 1-meter Duplex Single mode Fiber Patch Cable, LC/SC

### Features

- Manufactured from 9/125 duplex (zipcord) fiber
- PVC jacket
- Length: 1-meter. Connectors: 2 SC and 2 LC connectors on each end
- Insertion loss testing performed on every connector (0.2db typical) and provided with cable
- Beveled edge on ends of glass makes insertion of plug a breeze
- Fiber made from glass (not a polymer)
- Fiber optic distributed data interface (FDDI) rated
- OFNR (riser rated)

## Specifications

| OVERVIEW             |                  |
|----------------------|------------------|
| UPC Code             | 037332100535     |
| Technology           | Singlemode       |
| Optical Mode         | OS2              |
| CONNECTIONS          |                  |
| Side A - Connector 1 | LC DUPLEX (MALE) |
| Side B - Connector 1 | SC DUPLEX (MALE) |
| Endface Polish       | UPC              |
| PHYSICAL             |                  |
| Cable Jacket Color   | Yellow           |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                                                                 |
|--------------------------------------|-----------------------------------------------------------------|
| Connector Color                      | Blue; Blue; White                                               |
| Cable Jacket Material                | LSZH                                                            |
| Cable Jacket Rating                  | OFNR                                                            |
| Clad Diameter (microns)              | 125                                                             |
| Core Diameter (microns)              | 9                                                               |
| Number of Fibers                     | 2                                                               |
| Cable Length (ft.)                   | 3.3                                                             |
| Cable Length (m)                     | 1.01                                                            |
| Cable Length (in.)                   | 39.4                                                            |
| Minimum Bend Radius                  | 20 mm (Dynamic); 10 mm (Static)                                 |
| Shipping Dimensions (hwd / in.)      | 0.25 x 6.00 x 7.00                                              |
| Shipping Dimensions (hwd / cm)       | 0.64 x 15.24 x 17.78                                            |
| Shipping Weight (lbs.)               | 0.05                                                            |
| Shipping Weight (kg)                 | 0.02                                                            |
| Fiber Cable Length                   | 1M (3.3 ft)                                                     |
| <b>ENVIRONMENTAL</b>                 |                                                                 |
| Operating Temperature Range          | -4° to 140°F (-20° to 60°C)                                     |
| Storage Temperature Range            | -4° to 140°F (-20° to 60°C)                                     |
| Operating Humidity Range             | 5% to 85% RH, Non-Condensing                                    |
| Storage Humidity Range               | 35% to 65% RH, Non-Condensing                                   |
| <b>COMMUNICATIONS</b>                |                                                                 |
| Network Compatibility                | 1 Gbps (Gigabit); 10 Gbps; 25 Gbps; 40 Gbps; 100 Gbps; 400 Gbps |
| Attenuation @ 1310NM                 | 0.36 dB/km                                                      |
| Attenuation @ 1550NM                 | 0.22 dB/km                                                      |
| Insertion Loss                       | 0.30 dB                                                         |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                                                 |
| Push/Pull Tabs                       | No                                                              |
| Breakout                             | No                                                              |
| Trunk                                | No                                                              |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                                                 |
| Product Compliance                   | RoHS; REACH                                                     |
| <b>WARRANTY &amp; SUPPORT</b>        |                                                                 |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                        |                           |
|----------------------------------------|---------------------------|
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |
|----------------------------------------|---------------------------|

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.