

Straight Blade Devices, Receptacles,
Duplex, Industrial Grade, 2-Pole 3-Wire
Grounding, 20A 125V, 5-20R, Brown, Single
Pack

By Hubbell Wiring Device-Kellems
Catalog # [HBL5362](#)

Straight Blade Devices, Receptacles, Duplex, Industrial Grade, 2-
Pole 3-Wire Grounding, 20A 125V, 5-20R, Brown, Single Pack

Features

- Back wired ground terminal allows faster, easier installation
- One-piece brass integral ground strap
- Finder Groove Face
- Deep body design with circuit ID face

Application

Extra Heavy Duty Specification Grade

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - Top: UL 94V-2, Base: UL 94V-O, Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	5-20R
Industry Standard(s)	• Certified to CSA 22.2, No. 42 File 285 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
-----------------	------



Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	125 VAC
Wattage	2500 W
Connectivity	Back and Side Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20 A

Dimensions

Length	3.28 in
Display Size	Standard Sized Product
Weight	0.25 lb.
Height	1.19 in
Width	1.65 in
Dimensions	3.28 in x 1.65 in x 1.19 in

General

Color	Brown
Style	Finder Groove Face
Series	Extra Heavy Duty
Specifications	• Automatic Self-grounding Clip - Stainless steel • Base - PBT • By-Pass Power Contacts - .036 in. (.9) Brass • Clamping Plate - Nickel plated brass • Face - Nylon • Ground Contacts - .031 in. (.8) Brass • Mounting Screws - Zinc plated steel • Mounting Strap - .050 in. (1.3) Brass • Terminal Screws - Plated brass
UPC	783585435220
Type	Standard Duplex
Material - Mounting Hardware	Screw Mounting
Item Type	Traditional Duplex

Logistics

Pallet Quantity 3600
Carton Quantity 10

Product Assets

- Catalog [English]
- Catalog Page [English]
- Catalog Page [English]
- Installation Manual [English]

Operational

Operating Temperature Maximum continuous 75°C and minimum -40°C without Impact

Horsepower - Maximum 1



A Hubbell brand