

SiC MOSFET P3M12080K4

N-Channel Enhancement Mode

Features



- Qualified to AEC-Q101
- High Blocking Voltage with Low On-Resistance
- High-Frequency Operation
- Ultra-Small Q_{gd}

Benefits

- Improve System Efficiency
- Increase Power Density
- Reduce Heat Sink Requirements
- Reduction of System Cost

Applications

- Solar Inverters
- EV Battery Chargers
- High Voltage DC/DC Converters
- Switch Mode Power Supplies



TO-247-4

Drain	1
Power Source	2
Kelvin Source	3
Gate	4



Order Information

Part Number	Package	Marking
P3M12080K4	TO-247-4	P3M12080K4

Contents

Features.....	1
Benefits.....	1
Applications.....	1
Order Information	1
Contents.....	2
1. Maximum Ratings.....	3
2. Electrical Characteristics	4
3. Reverse Diode Characteristics.....	7
4. Thermal Characteristics.....	7
5. Typical Performance	8
6. Definitions	13
7. Package Outlines.....	14

PN Junction Semiconductor

1. Maximum Ratings

At $T_J = 25^\circ\text{C}$, unless specified otherwise

Parameter	Symbol	Value	Unit	Test Conditions
Drain - Source Voltage	V_{DSmax}	1200	V	$V_{GS} = -3\text{V}$ $I_D = 100\mu\text{A}$
Gate - Source Voltage (dynamic)	V_{GSmax}	-8 / +22	V	Duty cycle $\leq 1\%$
Gate - Source Voltage(static) turn-on gate voltage turn-off gate voltage	$V_{GS,on}$ $V_{GS,off}$	+15 / +18 -3	V	Static
Continuous Drain Current	I_D	39	A	$V_{GS} = 15\text{V}$ $T_C = 25^\circ\text{C}$
		27		$V_{GS} = 15\text{V}$ $T_C = 100^\circ\text{C}$
		40		$V_{GS} = 18\text{V}$ $T_C = 25^\circ\text{C}$
		28		$V_{GS} = 18\text{V}$ $T_C = 100^\circ\text{C}$
Pulsed Drain Current	$I_{D(pulse)}$	90	A	$PW \leq 10\mu\text{s}$, Duty cycle $\leq 1\%$
Power Dissipation	P_D	203	W	
Operating Junction	T_J	-55 To +175	$^\circ\text{C}$	
Storage Temperature	T_{stg}	-55 To +150	$^\circ\text{C}$	
Mounting Torque	M_d	1 8.8	Nm lbf-in	M3 or 6-32 screw

2. Electrical Characteristics

At $T_J = 25^\circ\text{C}$, unless specified otherwise

Parameter	Symbol	Value			Unit	Test Conditions
		Min.	Typ.	Max.		
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	1200	/	/	V	$V_{GS} = -3\text{V}$ $I_D = 0.5\text{mA}$
Gate Threshold Voltage	$V_{GS(th)}$	2.0	2.8	/	V	$V_{DS} = V_{GS}$ $I_D = 5\text{mA}$ $T_J = 25^\circ\text{C}$
		/	2.0	/	V	$V_{DS} = V_{GS}$ $I_D = 5\text{mA}$ $T_J = 175^\circ\text{C}$
Reverse Bias Drain Current	I_{DSS}	/	1	100	μA	$V_{GS} = -3\text{V}$ $V_{DS} = 1200\text{V}$
Gate-Source Leakage Current	I_{GSS}	/	2	125	nA	$V_{GS} = -5$ to 18V $V_{DS} = 0\text{V}$
Drain-Source On-State Resistance	$R_{DS(on)}$	/	80	98	m Ω	$V_{GS} = 15\text{V}$ $I_D = 20\text{A}$ $T_J = 25^\circ\text{C}$
		/	104	/		$V_{GS} = 15\text{V}$ $I_D = 20\text{A}$ $T_J = 175^\circ\text{C}$
		/	66	/		$V_{GS} = 18\text{V}$ $I_D = 20\text{A}$ $T_J = 25^\circ\text{C}$
		/	104	/		$V_{GS} = 18\text{V}$ $I_D = 20\text{A}$ $T_J = 175^\circ\text{C}$
Transconductance	g_{fs}	/	10	/	S	$V_{DS} = 20\text{V}$ $I_{DS} = 20\text{A}$ $T_J = 25^\circ\text{C}$
		/	9	/		$V_{DS} = 20\text{V}$ $I_{DS} = 20\text{A}$ $T_J = 175^\circ\text{C}$

Parameter	Symbol	Value			Unit	Test Conditions
		Min.	Typ.	Max.		
Input Capacitance	C_{iss}	/	1676	/	pF	$V_{GS} = 0V$ $V_{DS} = 800V$ $f = 1MHz$ $V_{AC} = 25mV$
Output Capacitance	C_{oss}	/	70	/		
Reverse Transfer Capacitance	C_{rss}	/	11	/		
Coss Stored Energy	E_{oss}	/	56	/	μJ	
Turn-on Energy	E_{on}	/	79	/	μJ	
Turn-off Energy	E_{off}	/	21	/		
Turn-On Delay Time	$T_{d(on)}$	/	22.7	/	ns	$V_{DS} = 800V$ $V_{GS} = -3/15V$ $I_D = 20A$ $R_G = 1\Omega$
Rise Time	T_r	/	12.3	/		
Turn-Off Delay Time	$T_{d(off)}$	/	30.7	/		
Fall Time	T_f	/	6.6	/		
Turn-on Energy	E_{on}	/	63	/	μJ	
Turn-off Energy	E_{off}	/	19	/		
Turn-On Delay Time	$T_{d(on)}$	/	20	/	ns	$V_{DS} = 800V$ $V_{GS} = -3/18V$ $I_D = 20A$ $R_G = 1\Omega$
Rise Time	T_r	/	10.6	/		
Turn-Off Delay Time	$T_{d(off)}$	/	19.3	/		
Fall Time	T_f	/	6.4	/		
Internal Gate Resistance	$R_{G(int)}$	/	2.1	/	Ω	$f = 1MHz$ $V_{AC} = 25mV$

Parameter	Symbol	Value			Unit	Test Conditions
		Min.	Typ.	Max.		
Gate to Source Charge	Q_{gs}	/	15.9	/	nC	$V_{DS} = 800V$ $I_{DS} = 20A$ $V_{GS} = -3/15V$ $I_G = 5mA$
Gate to Drain Charge	Q_{gd}	/	31	/		
Total Gate Charge	Q_g	/	56	/		
Gate to Source Charge	Q_{gs}	/	15.6	/		$V_{DS} = 800V$ $I_{DS} = 20A$ $V_{GS} = -3/18V$ $I_G = 5mA$
Gate to Drain Charge	Q_{gd}	/	33	/		
Total Gate Charge	Q_g	/	66	/		

PNJunction Semiconductor

3. Reverse Diode Characteristics

At $T_J = 25^\circ\text{C}$, unless specified otherwise

Parameter	Symbol	Value		Unit	Test Conditions
		Typ.	Max.		
Diode Forward Voltage	V_{SD}	5.3	/	V	$V_{GS} = -3\text{V}$ $I_{SD} = 10\text{A}$ $T_J = 25^\circ\text{C}$
		4.8	/	V	$V_{GS} = -3\text{V}$ $I_{SD} = 10\text{A}$ $T_J = 175^\circ\text{C}$
Continuous Diode Forward Current	I_S	/	37	A	$V_{GS} = -3\text{V}$
Reverse Recover Time	t_{rr}	23	/	ns	$V_{GS} = -3\text{V}/15$ $I_{SD} = 20\text{A}$
Reverse Recovery Charge	Q_{rr}	190	/	nC	$V_R = 800\text{V}$ $di/dt = 1500\text{A}/\mu\text{s}$
Peak Reverse Recovery Current	I_{rrm}	13.2	/	A	$T_J = 25^\circ\text{C}$
Reverse Recover Time	t_{rr}	21.6	/	ns	$V_{GS} = -3\text{V}/18$ $I_{SD} = 20\text{A}$
Reverse Recovery Charge	Q_{rr}	204	/	nC	$V_R = 800\text{V}$ $di/dt = 1500\text{A}/\mu\text{s}$
Peak Reverse Recovery Current	I_{rrm}	14.4	/	A	$T_J = 25^\circ\text{C}$

4. Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance from Junction to Case	$R_{\theta JC}$	0.74	$^\circ\text{C}/\text{W}$

5. Typical Performance

At $T_J = 25^\circ\text{C}$, unless specified otherwise




Figure 1. Output Characteristics $T_J = -55^\circ\text{C}$




Figure 2. Output Characteristics $T_J = 25^\circ\text{C}$




Figure 3. Output Characteristics $T_J = 125^\circ\text{C}$




Figure 4. Output Characteristics $T_J = 175^\circ\text{C}$




Figure 5. On-Resistance vs. Temperature




Figure 6. On-Resistance vs. Drain Current Various Temperatures




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Transfer Characteristic for Various Junction Temperatures




Figure 9. Body Diode Characteristic at -55°C




Figure 10. Body Diode Characteristic at 25°C




Figure 11. Body Diode Characteristic at 125°C




Figure 12. Body Diode Characteristic at 175°C




Figure 13. Threshold Voltage vs. Temperatures




Figure 14. Gate Charge Characteristics




Figure 15. 3rd Quadrant Characteristic at -55°C




Figure 16. 3rd Quadrant Characteristic at 25°C




Figure 17. 3rd Quadrant Characteristic at 125°C




Figure 18. 3rd Quadrant Characteristic at 175°C




Figure 19. Capacitances vs. Drain-Source Voltage (0 - 200V)




Figure 20. Capacitances vs. Drain-Source Voltage (0 - 1200V)




Figure 21. Maximum Power Dissipation Derating vs. Case Temperature




Figure 22. Output Capacitor Stored Energy




Figure 23. Clamped Inductive Switching Energy vs. Drain Current (VDD= 800V)




Figure 24. Clamped Inductive Switching Energy vs. RG(ext)




Figure 25. Clamped Inductive Switching Energy vs. Temperature




Figure 26. Switching Times vs. $R_{G(ext)}$




Figure 27. Transient Thermal Impedance (Junction - Case)




Figure 28. Safe Operating Area

6. Definitions




Figure 29. Turn-off Transient Definitions




Figure 30. Turn-on Transient Definitions




Figure 31. Reverse Recovery Definitions





Figure 32. V_{GS} Transient Definitions

7. Package Outlines



SYMBOL	DIMENSIONS		
	MIN.	NOM.	MAX.
A	4.83	5.02	5.21
A1	2.28	2.41	2.54
A2	1.91	2.00	2.16
b'	1.07	1.20	1.28
b	1.07	1.20	1.33
b1	2.39	2.67	2.94
b2	2.39	2.67	2.84
b3	1.07	1.30	1.60
b4	1.07	1.30	1.50
b5	2.39	2.53	2.69
b6	2.39	2.53	2.64
c	0.55	0.60	0.68
c1	0.55	0.60	0.65
D	23.30	23.45	23.80
D1	16.25	16.55	17.65
D2	0.95	1.19	1.25
E	15.75	15.94	16.13
E1	13.10	14.02	14.15
E2	3.60	4.40	5.10
E3	1.00	1.45	1.90
E4	12.38	13.26	13.43
●	2.54 BSC		
e1	5.08 BSC		
L	17.31	17.57	17.82
L1	3.97	4.19	4.37
L2	2.35	2.50	2.65
ΦP1	3.51	3.61	3.65
ΦP1	7.19 REF		
Q	5.49	5.79	6.00
S	6.04	6.17	6.30

Drawing and Dimensions

Important Notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, PN Junction hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

PN Junction reserves the right to make changes at any time to any products or information herein, without notice. "Typical" parameters which may be provided in PN Junction data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typical" must be validated for each customer application by customer's technical experts.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of PN Junction in customer's applications. The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest PN Junction office (www.pnjsemi.com).

Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest PN Junction office.

Except as otherwise explicitly approved by PN Junction in a written document signed by authorized representatives of PN Junction, PN Junction's products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.