


Extension Unit box 24" for mounting on all fully IP65-enclosed 16:9 HMI/IPC devices. Deep empty enclosure for the flexible installation of operator controls, (without pre-perforation)



| General information | |
|---|--|
| Product type designation | Extension Unit box 24" |
| Installation type/mounting | |
| Mounting | For mounting on a 16:9 HMI / IPC PRO device (lower part) |
| Mounting type | Screwed joint |
| Rack mounting | No |
| Front mounting | No |
| Supply voltage | |
| Type of supply voltage | DC |
| Rated value (DC) | 24 V |
| Degree and class of protection | |
| IP (all-round) | IP65 |
| NEMA (front) | |
| <ul style="list-style-type: none"> Enclosure Type 4 at the front | Yes |
| Standards, approvals, certificates | |
| RoHS conformity | Yes |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> min. max. | 0 °C 50 °C |
| Ambient temperature during storage/transportation | |
| <ul style="list-style-type: none"> min. max. | -20 °C 60 °C |
| Altitude during operation relating to sea level | |
| <ul style="list-style-type: none"> Installation altitude above sea level, max. | 2 000 m |
| Relative humidity | |
| <ul style="list-style-type: none"> Operation, max. | 90 %; no condensation |
| Mechanics/material | |
| Material | |
| <ul style="list-style-type: none"> Aluminum | Yes; Powder-coated |
| Enclosure material (front) | |
| <ul style="list-style-type: none"> Aluminum | Yes; Covered with black film |
| Dimensions | |
| Width | 583 mm |
| Height | 99 mm |
| Depth | 112 mm |
| Weights | |
| Weight (without packaging) | 3.1 kg |

| | |
|-----------------------------|--|
| Weight (with packaging) | 3.3 kg |
| Scope of supply | |
| Delivery quantity in pieces | 1 |
| Components included | Screws for attachment |
| Other | |
| Target devices | PRO devices for support arm (extendable, round tube) and pedestal (extendable, flange below) |
| last modified: | 4/21/2021  |