

6 PIN DIP RANDOM-PHASE TRIAC PHOTOCOUPLER

EL301x Series
EL302x Series
EL305x Series

Features:

- Peak breakdown voltage
 - 250V, EL301x
 - 400V, EL302x
 - 600V, EL305x
- High isolation voltage between input and output (Viso=5000 V rms)
- Compact dual-in-line package
- Pb free and RoHS compliant.
- UL approved ()
- VDE approved (pending)
- SEMKO approved (pending)
- NEMKO approved (pending)
- DEMKO approved (pending)
- FIMKO approved (pending)
- CSA approved (pending)



Description

The EL201x, EL302X and EL305x series products consist of GaAs infrared emitting diode optically coupled to a monolithic silicon random phase photo Triac.


They are designed for interfacing between electronic controls and power triacs to control resistive and inductive loads for 115 to 240 VAC operations.

Applications

- Solenoid/valve controls
- Lamp ballasts
- Static AC power switch
- Interfacing microprocessors to 115 to 240Vac peripherals
- Incandescent lamp dimmers
- Temperature controls
- Motor controls



Schematic



Pin Configuration

1. Anode
2. Cathode
3. No Connection
4. Terminal
5. No Connection
6. Terminal



LIGHTING FOREVER

6 PIN DIP RANDOM-PHASE TRIAC PHOTOCOUPLER

EL301x Series
EL302x Series
EL305x Series

Absolute Maximum Ratings ($T_a=25^{\circ}\text{C}$)

Parameter			Symbol	Rating	Unit
Input	Forward current		I _F	60	mA
	Reverse voltage		V _R	6	V
	Power dissipation		P _D	100	mW
Output	Off-state Output Terminal Voltage	EL301x	V _{DRM}	250	V
		EL302x		400	
		EL305x		600	
	Peak Repetitive Surge Current		I _{TSM}	1	A
	Power dissipation		P _D	300	mW
	Isolation voltage ^{*1}			V _{iso}	5000
Total power dissipation			P _D	330	mW
Operating temperature			T _{opr}	-55~+100	°C
Storage temperature			T _{stg}	-55~+125	°C
Soldering temperature ^{*2}			T _{sol}	260	°C

Notes

*1 AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1, 2 & 3 are shorted together, and pins 4, 5 & 6 are shorted together.

*2 For 10 seconds.



LIGHTING FOREVER

6 PIN DIP RANDOM-PHASE TRIAC PHOTOCOUPLER

EL301x Series
EL302x Series
EL305x Series

Electrical Characteristics ($T_a=25^{\circ}\text{C}$ unless specified otherwise)

Input

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
Forward voltage	V_F	-	1.18	1.5	V	$I_F = 10\text{mA}$
Reverse Leakage current	I_R	-	-	10	μA	$V_R = 6\text{V}$

Output

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
Peak Blocking Current	I_{DRM}	-	-	100	nA	$V_{\text{DRM}} = \text{Rated } V_{\text{DRM}}$ $I_F = 0\text{mA}$
Peak On-state Voltage	V_{TM}	-	-	2.5	V	$I_{\text{TM}}=100\text{mA peak, } I_F=\text{Rated } I_{\text{FT}}$
Critical Rate of Rise off-state Voltage	dv/dt	1000	-	-	$\text{V}/\mu\text{s}$	Fig.

Transfer Characteristics

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
LED Trigger Current	EL3010 EL3021 EL3051	-	-	15	mA	Main terminal Voltage=3V
	EL3011 EL3022 EL3052	-	-	10		
	EL3012 EL3023 EL3053	-	-	5		
Holding Current	I_H	-	250	-	μA	

* Typical values at $T_a = 25^{\circ}\text{C}$

6 PIN DIP RANDOM-PHASE TRIAC PHOTOCOUPLER

EL301x Series
EL302x Series
EL305x Series

Typical Performance Curves

Figure 1. Forward Current vs Forward Voltage




Figure 2. On-State Characteristics




Figure 3. Holding Current vs. Ambient Temperature




Figure 4. LED Current Required to Trigger vs. LED Pulse Width




Figure 5. Leakage Current vs. Ambient Temperature





Figure 6. LED Trigger Current vs. Ambient Temperature






LIGHTING FOREVER

6 PIN DIP RANDOM-PHASE TRIAC PHOTOCOUPLER

EL301x Series
EL302x Series
EL305x Series





LIGHTING FOREVER

6 PIN DIP RANDOM-PHASE TRIAC PHOTOCOUPLER

EL301x Series
EL302x Series
EL305x Series

Order Information

Part Number

EL301XY(Z)-V
or **EL302XY(Z)-V**
or **EL305XY(Z)-V**

Note

X = Part No. 3010 – 15mA, 3011 – 10mA, 3012 – 5mA

X = Part No. (1 for $I_{FT}=15mA$, 2 for $I_{FT}=10mA$, 3 for $I_{FT}=5mA$)

Y = Lead form option (S, S1, M or none)

Z = Tape and reel option (TA, TB or none).

V = VDE safety option


Option	Description	Packing quantity
None	Standard DIP-6	65 units per tube
M	Wide lead bend (0.4 inch spacing)	65 units per tube
S (TA)	Surface mount lead form + TA tape & reel option	1000 units per reel
S (TB)	Surface mount lead form + TB tape & reel option	1000 units per reel
S1 (TA)	Surface mount lead form (low profile) + TA tape & reel option	1000 units per reel
S1 (TB)	Surface mount lead form (low profile) + TB tape & reel option	1000 units per reel

6 PIN DIP RANDOM-PHASE TRIAC PHOTOCOUPLER


**EL301x Series
EL302x Series
EL305x Series**

Package Drawings (Dimensions in mm)

Standard DIP Type




Option M Type




6 PIN DIP RANDOM-PHASE TRIAC PHOTOCOUPLER

**EL301x Series
EL302x Series
EL305x Series**

Option S Type




Option S1 Type




6 PIN DIP RANDOM-PHASE TRIAC PHOTOCOUPLER

**EL301x Series
EL302x Series
EL305x Series**

Recommended pad layout for surface mount leadform



Device Marking



Notes


EL	denotes Everlight
3053	denotes Device Number
Y	denotes 1 digit Year code
WW	denotes 2 digit Week code
V	denotes VDE safety option (optional)

6 PIN DIP RANDOM-PHASE TRIAC PHOTOCOUPLER


**EL301x Series
EL302x Series
EL305x Series**

Tape & Reel Packing Specifications


Option TA



Option TB



Tape dimensions



Dimension No.	A	B	D0	D1	E	F
Dimension (mm)	10.4±0.1	7.52±0.1	1.5±0.1	1.5+0.1/-0	1.75±0.1	7.5±0.1

Dimension No.	P0	P1	P2	t	W	K
Dimension (mm)	4.0±0.15	1.6±0.1	2.0±0.1	0.35±0.03	16.0±0.2	4.5±0.1




LIGHTING FOREVER

6 PIN DIP RANDOM-PHASE TRIAC PHOTOCOUPLER

EL301x Series
EL302x Series
EL305x Series

Solder Reflow Temperature Profile



6 PIN DIP RANDOM-PHASE TRIAC PHOTOCOUPLER

**EL301x Series
EL302x Series
EL305x Series**

DISCLAIMER

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without the specific consent of EVERLIGHT.